

TAW10 - Week 1

1 At what point does the standard selection screen (as a result of a select-options) get displayed

---

- ✓ After Initialization event
- At Start-of-Selection event
- Before the Report Statement
- Prior to Initialization event

2 Where are authorizations managed for a given user

---

- In the users own data in the USER01 table
- ✓ In the user master record
- In the tauth table

3 How would you clear the body of an internal table (with a header line).

---

**(More than one answer is correct)**

- Refresh ITAB []
- Clear ITAB
- ✓ Refresh ITAB
- ✓ Clear ITAB[]

4 What are valid uses of a variant .

---

**(More than one answer is correct)**

- ✓ Pre-assigning values
- ✓ Hiding input fields
- Input validation
- Security checking

5 What does the following statement mean Write 'Hello'(001)

Write 'Hello' (001)

- This is not a valid statement
- Add the variable 'Hello' to message 001
- Write out 'Hello' and the contents of text element 001
- If Text Element 001 is not in your login language, then 'Hello' is displayed

6 What access methods are available for accessing internal tables.

---

**(More than one answer is correct)**

- Standard
- Index
- Hashed
- Key
- Sorted

7 What is true about trapping errors with the Catch statement

---

- A data variable defined with type X must be defined to receive the raised error code
- The statement immediately following the CATCH statement is executed in the event of an error trapped by the CATCH statement
- A CASE statement can be used to validate the value of the error class
- An Endcatch statement is required

8 What is the structure of the internal table when a select-options is declared in your program.

---

- Low High Sign Option
- Sign Operator High Low
- Sign Option Low High
- High Low Sign Operator

9 Mark the valid syntax and usage of the message statement. Assume the message class UD is defined in the REPORT statement.

**(More than one answer is correct)**

- ✓ Message E004(UD)
- Message (UD)E004
- ✓ Message E004
- ✓ Message ID UD Type E Number 0004

10 On the Program Attributes screen, mark the fields that are mandatory when creating a program.

---

**(More than one answer is correct)**

- ✓ Program Name
- Title
- Status
- Application
- ✓ Type

TAW10 - Week 1

11 What is the value of result after the following code is executed

---

```
DATA: result TYPE I.
```

```
result = 5 / 10.
```

- ✓ result = 1
- result = 0
- result = 2
- result = .5

12 What program type can be executed directly

---

- ✓ Executable
- Include
- Class
- Function Group

13 What is the customer allowed naming convention for lock objects

---

- ENQUEUE\* or DEQUEUE\*
- ZE\* or YE\*
- ✓ EZ\* or EY\*
- Z\* or Y\*

14 Identify the ABAP numeric data types.

---

**(More than one answer is correct)**

- ✓ X
- I
- N
- D
- ✓ F
- ✓ P

15 How could you retrieve a single entry from MYTABLE . (Key fields are number, name)

---

- Select \* from MYTABLE where number = '01' Endselect.
- Select \* from MYTABLE where number = '01' and name = 'LISA'.
- ✓ Select single \* from MYTABLE where number = '01' and name = 'LISA'.
- Select single \* from MYTABLE with keys

16 What is the result of the following date calculation. Assume current date is 20001220

---

Data: Today(8) type C.

Today = sy-datum.

Today = 10.

- 20011210
- 20001220
- 10001220
- ✓ 10

17 What is the default length for Integer Data Types

---

- size must be specified
- ✓ 4
- 1
- 2

18 Structure MY\_STRUCTURE is created in the dictionary. When does the structure get created in the underlying database

---

- At the end of the table creation after it is saved.
- When the table is activated
- At the beginning of the table creation
- ✓ It does not correspond to an object in the underlying database and does not get created
- When the database administrator physically creates the table

19 Which addition to the Parameters statement is not valid

---

- ✓ Like
- Value
- Type
- Default

20 Where are authorizations managed for a given user

---

- In the tauth table
- In the users own data
- in the USER01 table
- ✓ In the user master record

## TAW10 - Week 1

21 What is true about PARAMETER objects in ABAP.

---

- ✓ Parameter objects are a maximum of 30 characters in length
- You can use text elements with parameters
- Lower Case is the default

22 How much memory is reserved for the data object input\_record in the following statement.

---

```
Types: begin of rec_type,
        flag      type c,
        count(3) type c,
        today     type d,
        end of rec_type.
```

```
Data: input_record type rec_type.
```

- 0 bytes
- 4 bytes
- ✓ 12 bytes
- 5 bytes

23 Where does the message get issued in the following.

---

```
Report ZPROGA.
Data: fielda type c.
```

```
Call Function Z_TEST_FUNCTION
  Exporting fielda = fielda
  Exceptions No_Entry = 01
             Failure  = 02.
```

```
If sy-subrc = 01.
  Message E123.
Endif.
```

```
Function Z_TEST_FUNCTION
  Importing  f_fielda
  Exporting  f_fieldb
  Exceptions No_Entry
             Failure
```

## TAW10 - Week 1

Message E123 Raising No\_Entry

- ✓ In Program ZPROGA  
It will abend in the runtime system  
In Function Z\_TEST\_FUNCTION  
In Program ZPROGA and Function Z\_TEST\_FUNCTION

24 What is the default length for Integer Data Types

---

- ✓ 1  
size must be specified
- ✓ 4
- 2

25 How many dialog steps in an SAP Transaction.

---

- ✓ Only One  
One for every transaction in the SAP LUW  
One for every explicit database commit
- At least One

26 Which of the following allocates memory

---

- ✓ Data Type
- Data Object
- Dictionary Type
- Report Statement

27 Refer to the following Code. What is the value of sy-fdpos and sy-subrc after the search is executed

---

```
Data: mystring type c value 'SAPDOMAIN'.
```

```
Search mystring for 'X'
```

- ✓ sy-fdpos = 0 and sy-subrc = 4
- sy-fdpos = 0 and sy-subrc = 0
- sy-fdpos = 4 and sy-subrc = 0
- sy-fdpos = 4 and sy-subrc = 4



28 Which tool is used to manage and organize development objects

---

- ✓ WorkBench Organizer
- Customizing Organizer
- Information System
- Repository Browser

29 What part of an SAP system is responsible for converting OPEN SQL statements to Native SQL

---

- ✓ Basis System
- ABAP Interpreter
- Database Interface
- Database Server
- Dispatcher

30 What is a R/3 system

---

- Multiple Application Servers
- Instance plus system services
- Database
- ✓ Instance plus Database

TAW10 - Week 1

31 Where is spool request data stored

---

- on the database server
- on the operating system
- on the application server
- ✓ on the TEMSE database

32 Which service is responsible for communication between distributed dispatchers

---

- gateway
- communication
- dialog
- ✓ message

33 Assuming you have created a data object of type c with the name ZFIELDA in your program. Which of the following is allowed

---

- ✓ Data: ZFIELDA type n
- Types: ZFIELDA type I
- Data: ZFIELDA type c
- Constants: ZFIELDA type n

34 Mark the item that is not a valid work process

---

- ✓ Gateway
- Spool
- Update
- Background

35 How could you retrieve a single entry from MYTABLE . (Key fields are number, name)

---

Select \* from MYTABLE where number = '01' Endselect.  
Select \* from MYTABLE where number = '01' and name = 'LISA'.

- ✓ Select single \* from MYTABLE with keys
- ✓ Select single \* from MYTABLE where number = '01' and name = 'LISA'.

36 When does an object get generated

---

- ✓ When the program is loaded
- ✓ When a CREATE OBJECT statement is processed
- When the reference variable for the class is defined
- When a method of an object is called

37 Identify the element that is not part of the user interface

---

- ✓ standard toolbar
- ✓ selection screen
- Function key settings
- menu bar
- title bar
- application toolbar

38 Static data records that have a long life are considered to be:

---

- ✓ Master Data
- Transactional data
- Customer documents
- Client data

39 In what case would you typically use a NUMC field

---

- ✓ Where there is a need for numbers, characters, and arithmetic operations
- ✓ Where only numbers are allowed and there is no need for arithmetic operations

## TAW10 - Week 1

Where only numbers are allowed and there is a need for arithmetic operations

40      Where are authorizations managed for a given user

- ✓      In the user master record  
in the USER01 table
- In the users own data
- In the tauth table

## TAW10 - Week 1

41 Identify the processing blocks of an ABAP program

---

**(More than one answer is correct)**

- ✓ Event
- ✓ Dialog Module
- Declarations
- Function

42 Identify the includes that would get generated if your program name is SAPMZYPROGRAM

---

- SAPMZYPROGRAMTOP
- MZMYPROGRAMDATA
- SAPMZYPROGRAM
- MZMYPROGRAMINCLUDE
- ✓ MZMYPROGRAMTOP

43 Which statement is valid for processing internal table itab.Data: itab type table of zmytab with header line.

---

- Loop where itab-id = A .Endloop.
- ✓ Loop at itab where id = A .Endloop.
- Loop at itab.Endtab.
- Loop at itab where itab-id = A .Endloop.

44 How would you set breakpoints in your program for debugging.

---

**(More than one answer is correct)**

- Start program in background mode
- ✓ Put a break-point statement in your program code
- In Development workbench, set breakpoint
- ✓ In the program editor, set breakpoint

45 Mark the item that is not a valid work process

---

- Background
- Update
- Spool
- ✓ Gateway

46 Assuming you have created a data object of type c with the name ZFIELDA in your program. Which of the following is allowed

---

- Constants: ZFIELDA type n
- Data: ZFIELDA type c
- ✓ Types: ZFIELDA type I
- Data: ZFIELDA type n

47 How would you determine the program name currently being executed

---

- F4
- F9
- ✓ Use menu option System>Status
- Look in the dictionary

48 What is the default mode for passing actual parameters in a Perform

---

- ✓ By Changing
- By Reference
- By Value

49 In the Catch statement, What is every runtime error assigned to

---

- ✓ Error Class
- Catch Class
- Development Class
- Case

50 Name the layers of the R/3 architecture.

---

**(More than one answer is correct)**

- ✓ Communication
- ✓ Internet
- ✓ Database
- ✓ Presentation
- ✓ Application

## TAW10 - Week 1

51 What must be assigned to a module pool in order for it to be executed

---

- ✓ Transaction
- Event
- Module
- Program Type

52 What is true about classes and objects in Object Oriented ABAP

---

**(More than one answer is correct)**

- ✓ Classes are an instance of an object
- ✓ Class is a template for an object
- Objects can change their class
- ✓ Objects are an instance of a class

53 What must be assigned to search help parameters

---

- ✓ data element
- values
- domain
- nothing

54 Where does the message get issued in the following.

---

```
Report ZPROGA.
Data: fielda type c.

Call Function Z_TEST_FUNCTION
  Exporting fielda = fielda
  Exceptions No_Entry = 01
            Failure   = 02.

If sy-subrc = 01.
  Message E123.
Endif.
```



## TAW10 - Week 1

```
Function Z_TEST_FUNCTION
  Importing    f_fielda
  Exporting    f_fieldb
  Exceptions   No_Entry
              Failure
```

Message E123 Raising No\_Entry

- ✓ It will abend in the runtime system  
In Program ZPROGA  
In Function Z\_TEST\_FUNCTION  
In Program ZPROGA and Function Z\_TEST\_FUNCTION

55 What method of Class CL\_GUI\_ALV\_GRID would be used to display the contents of an internal table

---

- ✓ REFRESH\_TABLE\_DISPLAY  
SET\_TABLE\_FOR\_DISPLAY  
CONSTRUCTOR  
SET\_TABLE\_FOR\_FIRST\_DISPLAY

56 What has happened if an authorization fails with sy-subrc = 4

---

- ✓ The user has an authorization containing the required values  
The user does not have the required authorization  
The authorization check used the incorrect authorization object

57 What is true about PARAMETER objects in ABAP.

---

- ✓ Lower Case is the default  
Parameter objects are a maximum of 30 characters in length  
You can use text elements with parameters

58 What is the icon that represents a breakpoint

---

highlighted line  
warning sign

- ✓ info sign  
stop sign

59 What can occur if a conversion rule does not exist for fields of incompatible data types

---

**(More than one answer is correct)**

- ✓ A syntax error for statically defined fields
- A syntax error for dynamically defined fields
- A run time error for statically defined fields
- ✓ A run time error for dynamically defined fields

60 What is the result of the following code. Assume there are 5 records in itab.

---

```
Loop at itab.  
  ctr = ctr + 1  
  write: sy-tabix.  
  check ctr = 3.  
  delete itab  
endloop.
```

- 1 2 3 4
- 1 2 4 5
- 1 2 3 4 5
- ✓ 1 2 3 3 4

TAW10 - Week 1

61 How would you clear the body of an internal table (with a header line).

---

**(More than one answer is correct)**

- ✓ Refresh ITAB
- Clear ITAB
- ✓ Clear ITAB[]
- Refresh ITAB []

62 How is security handled at the application level

---

- ✓ The authorization concept is used to restrict access to data and transactions
- The authorization concept is used to restrict access to users
- The authorization concept is used to restrict access to servers and work processes
- The authorization concept is used to restrict access to the dictionary

63 When does an object get generated

---

- When the reference variable for the class is defined
- When a method of an object is called
- When the program is loaded
- ✓ When a CREATE OBJECT statement is processed

64 What is the icon that represents a breakpoint

---

- ✓ stop sign
- warning sign
- highlighted line
- info sign

65 Assuming you have created a data object of type c with the name

ZFIELDA in your program. Which of the following is allowed

---

- ✓ Types: ZFIELDA type I  
Data: ZFIELDA type c  
Data: ZFIELDA type n  
Constants: ZFIELDA type n

66 What is true about trapping errors with the Catch statement

---

- ✓ The statement immediately following the CATCH statement is executed in the event of an error trapped by the CATCH statement
- ✓ A CASE statement can be used to validate the value of the error class
- ✓ A data variable defined with type X must be defined to receive the raised error code
- ✓ An Endcatch statement is required

67 What system variable is reset at the exit of a loop of an internal table.  
i.e. Loop at itab. ... Endloop.

---

- ✓ SY-INDEX
- ✓ SY-DBCNT
- ✓ SY-LOOP
- ✓ SY-TABIX

68 Select the valid types of user dialogs

---

**(More than one answer is correct)**

- ✓ Screens
- ✓ Logical Database
- ✓ Business Objects
- ✓ Selection Screen
- ✓ Lists

69 You are in screen painter. What is a requirement when assigning program fields to the screen

the fields attributes have to be manually defined in the screen painter

the data objects must be activated

data objects must be activated in the dictionary

✓ the program must be activated

70 What is the effect of sorting a sorted internal table

---

✓ Syntax error  
Uses linear search rather than binary  
Breaks the sort sequence  
Program abend

## TAW10 - Week 1

- 71 What will be written to the list in the following code. Assume all defaults are taken when the function was defined.
- 

```
Data: fielda(4) type c.  
fielda = AAAA .
```

```
Call Function Z_TEST_FUNCTION  
Exporting f_fielda = fielda.
```

```
Write fielda.
```

```
Function Z_TEST_FUNCTION  
Importing f_fielda  
Exporting f_fieldb
```

```
f_fielda = BBBB .  
f_fieldb = CCCC
```

✓ AAAA  
BBBB  
CCCC

- 72 Where is the statement
- 

✓ In a PAI Module  
In a Function  
Anywhere in the program  
In a Form Only

- 73 Identify the standard buffer setting for context objects
- 

✓ Permanent  
Temporary  
No  
Shared

- 74 Identify the processing blocks of an ABAP program
-

(More than one answer is correct)

- ✓ Function
- ✓ Event
- ✓ Declarations
- ✓ Dialog Module

75 What should be performed after an R3 upgrade

---

- ✓ Run SPAU to adjust change requests
- ✓ Run SPDD to adjust dictionary objects
- ✓ Release all Change Requests
- ✓ Run RDDMASGO

76 Refer to the following Code. What is the value of sy-fdpos and sy-subrc after the search is executed

---

```
Data: mystring type c value 'SAPDOMAIN'.
```

```
Search mystring for 'X'
```

- ✓ sy-fdpos = 4 and sy-subrc = 0
- ✓ sy-fdpos = 0 and sy-subrc = 0
- ✓ sy-fdpos = 0 and sy-subrc = 4
- ✓ sy-fdpos = 4 and sy-subrc = 4

77 Identify the only method found in class CL\_GUI\_CUSTOM\_CONTAINER

---

- ✓ Destructor
- ✓ Class
- ✓ Constructor
- ✓ Refresh

78 What possibilities are made available to the user when using selection screens

---

**(More than one answer is correct)**

- ✓ Variants
- ✓ Complex Entries
- Menu trees
- Translation Utilities
- ✓ Type Checks

79 Which is NOT a valid TYPE definition

---

**(More than one answer is correct)**

- Types: t\_mytab type lfa1.
- ✓ Types: t\_mytab type lfa1 of standard table.
- ✓ Type: t\_mytab type lfa1.
- Types: t\_mytab like lfa1.

80 What is the icon that represents a breakpoint

---

- ✓ info sign
- stop sign
- highlighted line
- warning sign



TAW10 - Week 1

81 What are the tasks of the dispatcher.

---

**(More than one answer is correct)**

- ✓ performing program syntax checks
- ✓ distributing transaction load
- ✓ assigning users to work processes
- ✓ organizing communication

82 Identify the servers of which only one can exist in an R/3 system.

---

**(More than one answer is correct)**

- ✓ One message server
- ✓ One application server
- ✓ One enqueue server
- ✓ One database server
- One presentation server

83 Which addition to the Parameters statement is not valid

---

- ✓ Default  
Type  
Value  
Like

84 How is security handled at the application level

---

- ✓ The authorization concept is used to restrict access to users
- The authorization concept is used to restrict access to data and transactions
- The authorization concept is used to restrict access to the dictionary
- The authorization concept is used to restrict access to servers and work processes

85 What is a client in an R/3 system

---

- ✓ Vendor
- Customer
- Organizational unit
- Delivered by Sap

86 What does the runtime system do with dates if they are assigned to a numeric field

---

- ✓ It calculates the number of days that have elapsed since 01.01.0001
- It converts the date to a julian date
- It calculates the number of days that have elapsed since 00.00.0000
- It leaves the date as a numeric field

87 What are field symbols used for

---

- ✓ for re-assigning field types
- for referencing an address of a field
- for graphic symbols on screens and lists
- for referencing multiple fields at the same time

88 What program type can be run directly

---

- ✓ Interface Pool
- Executable
- Runnable
- Module Pool

89 What is the default length for Integer Data Types

---

- ✓ 2  
4  
size must be specified

90 A data element is an example of

---

- ✓ Technical Domain  
Semantic Domain  
Business Object  
Physical Definition

## TAW10 - Week 1

91 What interface protocol is RFC based on

---

- ✓ LU6.2
- CPI-C
- SNA
- TCP/IP

92 What is written to the report in the following code

---

```
Data: Fielda type i value 1.
Perform Calculate_Sales.
Fielda = fielda + 1.
write:/ fielda.
```

```
Form Calculate_Sales.
  Data: Fielda type I value 2.
  Fielda = Fielda + 2.
Endform.
```

- 3
- 5
- 4
- 1
- ✓ 2

93 What is the value of ZFIELDDB after the last line of the following code is executed

---

```
Data: ZFIELDA(5) type c value 'ABCDE'.
      ZFIELDDB(4) type c.
```

```
ZFIELDA = XX .
Clear ZFIELDA.
ZFIELDDB = ZFIELDA.
```

- BCDE
- ABCDE
- ✓ Spaces
- ABCD

94 What are valid uses of a variant .

**(More than one answer is correct)**

- ✓ Pre-assigning values
- Input validation
- Security checking
- ✓ Hiding input fields

95 Which fields are used for sorting the internal table itab in the following code

---

```
Types: begin of itab_structure,  
        Field1 type p,  
        Field2 type c,  
        Field3 type I,  
        Field4 type n,  
        end of itab_structure.
```

```
Data: itab type table of itab_structure.
```

```
Sort itab.
```

- Field2
- Field1, Field3
- Field1
- ✓ Field2, Field4

96 Select the one item that is not a SAP Default Navigation Button on a standard list

---

- ✓ Cut/Paste
- Back/Exit/Cancel
- Save
- Find

97 Which software component in the work process is responsible for controlling commits and rollbacks

---

- Screen Processor
- ABAP Processor
- Dialog Processor

✓ Database Interface

98 Identify the rules involved when calling subroutines

---

**(More than one answer is correct)**

When calling by value, the address of the actual parameter is passed to the form

Optional parameters are allowed

✓ The number of actual and formal parameters must be the same

✓ Type checking is performed on parameters

99 What is true about an Authorization Object ?

---

✓ Groups up to 10 authorization fields in an OR relationship

Groups up to 10 authorization fields in an AND relationship

Authorization Objects contain permissible values for the fields

100 Standard and sorted tables are referred to as

---

non unique

keyed

generic

✓ index

Unique

## TAW10 - Week 1

101 An Authorization Object can contain how many authorization fields

---

- ✓ 10
- unlimited
- defined by Basis
- 0

102 What is true about PARAMETER objects in ABAP.

---

- ✓ You can use text elements with parameters
- Parameter objects are a maximum of 30 characters in length
- Lower Case is the default

103 What statement will clear the entire contents of the internal table itab that has no header line.

---

```
Types: begin of itab_structure,
        Field1 type p,
        Field2 type c,
        Field3 type I,
        Field4 type n,
end of itab_structure.
```

```
Data: itab type standard table of itab_structure.
Data: wa_itab type itab_structure.
```

- Clear wa\_itab
- Initialize itab
- ✓ Clear itab
- Initialize wa\_itab

104 Define Instance.

---

work processes only  
 a presentation, application and database server  
 Multiple application servers

✓ dispatcher, work processes, and services

105 What determines the sequence in which events blocks are processed

---

The Programmer  
The User  
The Dispatcher  
✓ The run time system

106 Where are authorizations managed for a given user

---

✓ In the user master record  
In the tauth table  
In the users own data  
in the USER01 table

107 Identify the includes that would get generated if your program name is SAPMZYPROGRAM

---

✓ MZMYPROGRAMINCLUDE  
MZMYPROGRAMTOP  
SAPMZYPROGRAM  
SAPMZYPROGRAMTOP  
MZMYPROGRAMDATA

108 Mark the valid statement for reading an entry from an internal table of type sorted

---

Read Table itab with sorted key k1  
Read Table itab by binary key k1  
✓ Read Table itab with Table Key K1  
Read Table itab by key K1

109 Static data records that have a long life are considered to be:

---



Client data  
Transactional data  
Customer documents  
Master Data



110 What does the following statement mean Write 'Hello'(001)

---

Write 'Hello' (001)

This is not a valid statement  
Add the variable 'Hello' to message 001  
If Text Element 001 is not in your login language, then  
'Hello' is displayed  
Write out 'Hello' and the contents of text element 001



TAW10 - Week 1

111 If you want the debugger to stop when the value of 'fielda' changes. Which option would you set in the debugger

---

- Object
- Overview
- Fields
- ✓ WatchPoint

112 What internal table type can only be accessed by its key

---

- Sorted
- Standard
- Keyed
- ✓ Hashed

113 What is true about an Authorization

---

**(More than one answer is correct)**

- ✓ It is attached to profiles
- ✓ Defines permissible values for each authorization field listed in the authorization object
- An authorization is defined in the program attributes

114 Mark the item that is not a valid work process

---

- ✓ Gateway
- Background
- Spool
- Update

115 What requirement exists if a field is defined in the dictionary of type CURR

- ✓ The field must be numeric
- Decimals must be defined in the domain
- ✓ The field must be linked to another field of type CUKY
- No other requirement exists

116 What event is used to create detail lists

---

- ✓ Initialization
- At Line-Selection
- New-Page
- Suppress Dialog
- On Detail

117 When does an object get generated

---

- When the program is loaded
- When the reference variable for the class is defined
- When a method of an object is called
- ✓ When a CREATE OBJECT statement is processed

118 Static data records that have a long life are considered to be:

---

- ✓ Customer documents
- Master Data
- Transactional data
- Client data

119 What will be written to the list in the following code. Assume all defaults are taken when the function was defined.

---

```
Data: fielda(4) type c.  
fielda = AAAA .
```

```
Call Function Z_TEST_FUNCTION  
Exporting f_fielda = fielda.
```

```
Write fielda.
```

```
Function Z_TEST_FUNCTION  
Importing f_fielda  
Exporting f_fieldb
```

```
f_fielda = BBBB .  
f_fieldb = CCCC
```

✓ BBBB  
CCCC  
AAAA

120 What part of an SAP system is responsible for converting OPEN SQL statements to Native SQL

---

✓ Basis System  
Database Interface  
Database Server  
ABAP Interpreter  
Dispatcher

## TAW10 - Week 1

121 Where is the record inserted in the internal table itab.

---

```
Types: begin of itab_structure,
       Field1 type p,
       Field2 type c,
       Field3 type I,
       Field4 type n,
       end of itab_structure.
```

```
Data: itab type standard table of itab_structure.
Data: wa_itab type itab_structure.
```

```
Insert wa_itab into table itab.
```

- At the beginning
- in the correct sorted position
- ✓ At the end
- It can't be done

122 How many dialog steps in an SAP Transaction.

---

- One for every explicit database commit
- ✓ At least One
- One for every transaction in the SAP LUW
- Only One

123 How many column headers are displayed on the screen in a standard list

---

- ✓ 2
- 4
- There are no column headers
- 1

124 Which is not a type of RFC call

---

- ✓ Remote

Transactional  
Asynchronous  
Synchronous

125 What is a valid configuration for an R3 System.

---

**(More than one answer is correct)**

- ✓ One Application server and one Database server
- ✓ Many Application servers and one Database server
- One Application server and many Database servers
- No Application server and one Database server

126 What is true about PARAMETER objects in ABAP.

---

- Lower Case is the default
- Parameter objects are a maximum of 30 characters in length
- ✓ You can use text elements with parameters

127 Select the valid types of user dialogs

---

**(More than one answer is correct)**

- ✓ Lists
- ✓ Screens
- ✓ Selection Screen
- Logical Database
- Business Objects

128 What program type can be executed directly

---

- ✓ Function Group
- Executable
- Class
- Include

129 What requirement exists if a field is defined in the dictionary of type CURR

---

- Decimals must be defined in the domain
- The field must be numeric
- No other requirement exists
- ✓ The field must be linked to another field of type CUKY

130 What is written to the report in the following code

---

```
Data: Fielda type i value 1.  
Perform Calculate_Sales.  
Fielda = fielda + 1.  
write:/ fielda.
```

```
Form Calculate_Sales.  
  Data: Fielda type I value 2.  
  Fielda = Fielda + 2.  
Endform.
```

- 5
- 4
- 1
- 3
- ✓ 2

## TAW10 - Week 1

131 Which use of the FORM statement works successfully when passing IT to FORMA

---

Types: Begin of line,

...

End of Line.

Types IT\_LINE Type Standard table of line.

Data IT TYPE IT\_LINE.

Perform FORMA using IT

- FORM FORMA Using P\_IT like IT\_LINE
- FORM FORMA Using P\_IT like LINE
- FORM FORMA Using P\_IT like LINE
- ✓ FORM FORMA Using P\_IT type IT\_LINE

132 What is the default length for Integer Data Types

---

- 2
- 1
- ✓ 4
- size must be specified

133 How would you clear the body of an internal table (with a header line).

---

**(More than one answer is correct)**

- ✓ Clear ITAB[]
- Refresh ITAB []
- ✓ Refresh ITAB
- Clear ITAB

134 Which Basis configuration would typically run on one server

---

- 2 Tier Presentation
- 3 Tier
- Database



✓ Central

135 What has happened if an authorization fails with sy-subrc = 4

---

The user has an authorization containing the required values  
The authorization check used the incorrect authorization object

✓ The user does not have the required authorization

136 What is meant by the software oriented client/server model.

---

✓ Server and client are both located on the same software  
Client responds to a server request regardless of hardware  
Server responds to a client request regardless of hardware  
Server and client are both located on the same hardware platform

137 Which is not a valid R3 configuration

---

✓ Three Tier  
Single Database  
Two tier client server  
Central

138 A data element is an example of

---

Physical Definition  
Technical Domain  
Business Object  
✓ Semantic Domain

139 What requirement exists if a field is defined in the dictionary of type CURR

---

- ✓ The field must be numeric
- ✓ The field must be linked to another field of type CUKY
- ✓ Decimals must be defined in the domain
- ✓ No other requirement exists

140 What does workflow achieve

---

**(More than one answer is correct)**

- ✓ manages communication media
- ✓ controls information flow
- ✓ builds screen sequences
- ✓ automates execution of activities

## TAW10 - Week 1

141 What is the role of the dispatcher

---

- Issues SQL requests to the underlying database
- Manages services between R/3 systems
- Dispatches tasks to non R3 systems
- ✓ Controls resources for the R/3 applications

142 Standard and sorted tables are referred to as

---

- keyed
- generic
- Unique
- non unique
- ✓ index

143 Static data records that have a long life are considered to be:

---

- Client data
- Customer documents
- Transactional data
- ✓ Master Data

144 Where is the record inserted in the internal table itab.

---

```
Types: begin of itab_structure,
        Field1 type p,
        Field2 type c,
        Field3 type I,
        Field4 type n,
        end of itab_structure.
```

```
Data: itab type standard table of itab_structure.
Data: wa_itab type itab_structure.
```

```
Insert wa_itab into table itab.
```

in the correct sorted position

- ✓ At the beginning
- At the end
- It can't be done

145 When creating a function using the function builder, you can set the attribute of the function to determine its processing type. What are the available processing types.

---

**(More than one answer is correct)**

- ✓ Normal
- ✓ Remote-enabled
- Non Updateable
- Enabled
- ✓ Update

146 What is true about PARAMETER objects in ABAP.

---

- Parameter objects are a maximum of 30 characters in length
- ✓ You can use text elements with parameters
- Lower Case is the default

147 What is the effect of the EXIT statement in the following code

---

```
Report ABC
Data: ..

Start-of-Selection.
Perform Form A.
End-of-Selection.

Form A.
  Loop at inttab.
    ...
    Exit.
  Endloop.
Endform.
```

- Exits the Program
- ✓ Exits the Loop
- Exits the Start-of-Selection Event
- Exits the Form

148 Which use of the FORM statement works successfully when passing IT to FORMA

---

Types: Begin of line,

...

End of Line.

Types IT\_LINE Type Standard table of line.

Data IT TYPE IT\_LINE.

Perform FORMA using IT

- ✓ FORM FORMA Using P\_IT type IT\_LINE
- FORM FORMA Using P\_IT like LINE
- FORM FORMA Using P\_IT like LINE
- FORM FORMA Using P\_IT like IT\_LINE

149 What are valid uses of a variant .

---

**(More than one answer is correct)**

- ✓ Pre-assigning values
- Security checking
- ✓ Hiding input fields
- Input validation

150 Where does information come from when you press F1 on a screen field

---

- ✓ Data element documentation
- Domain short text
- Domain Help values
- Search help

## TAW10 - Week 1

- 151 At what point does the standard selection screen (as a result of a select-options) get displayed
- 
- ✓ Before the Report Statement  
After Initialization event  
Prior to Initialization event  
At Start-of-Selection event
- 152 Mark the item that is not true about the Catch..EndCatch statement
- 
- the return value assigned to the system exception is stored in sy-subrc  
the Others option catches any runtime errors not already assigned  
✓ a runtime error in a form called within a catch block is caught  
a runtime error causes the system to go to the ENDCATCH statement
- 153 What statement is used to move identically named fields between structures
- 
- ✓ ASSIGN  
MOVE\_CORRESPONDING  
MOVE-CORRESPONDING  
MOVE
- 154 An ABAP program makes calls to function modules from the same function group. What happens with the Global data from the function group
- 
- (More than one answer is correct)**
- ✓ Function modules from the same function group can access the global data when they are called

- ✓ The global data remains available for the duration of the calling program
- The global data is reinitialized for each new call
- The global data remains active for the duration of the function call only

155 What menu options are available on all screens.

---

**(More than one answer is correct)**

- ✓ Help
- Options
- ✓ System
- Status
- Tools

156 What is true about classes and objects in Object Oriented ABAP

---

**(More than one answer is correct)**

- Classes are an instance of an object
- Objects can change their class
- ✓ Class is a template for an object
- ✓ Objects are an instance of a class

157 What is the customer namespace for Functions

---

- F
- FZ
- ✓ Y\_ or Z\_
- Y or Z

158 How is security handled at the application level

---

- The authorization concept is used to restrict access to the dictionary
- The authorization concept is used to restrict access to users

## TAW10 - Week 1

The authorization concept is used to restrict access to servers and work processes

- ✓ The authorization concept is used to restrict access to data and transactions

159 What does workflow achieve

---

**(More than one answer is correct)**

- ✓ automates execution of activities
- manages communication media
- builds screen sequences
- ✓ controls information flow

160 Mark the valid use of the data statement. Assume that ZBOOK-ID is a dictionary object

---

- ✓ Data fielda like zbook-id
- Data fielda type c like zbook-id
- Data fielda value zbook-id
- Data fielda(5) like zbook-id



## TAW10 - Week 1

161 Which tool is used to manage and organize development objects

---

- Information System
- Repository Browser
- ✓ WorkBench Organizer
- Customizing Organizer

162 What is the effect when a CLEAR statement is used on an internal table without header line

---

- Nothing
- All the lines of the table are initialized
- ✓ All the lines of the table are deleted
- The work area is initialized

163 In the Catch statement, What is every runtime error assigned to

---

- Case
- Catch Class
- ✓ Error Class
- Development Class

164 What can occur if a conversion rule does not exist for fields of incompatible data types

---

**(More than one answer is correct)**

- ✓ A syntax error for statically defined fields
- A syntax error for dynamically defined fields
- ✓ A run time error for dynamically defined fields
- A run time error for statically defined fields

165 What has happened if an authorization fails with sy-subrc = 4

- ✓ The authorization check used the incorrect authorization object
- The user has an authorization containing the required values
- ✓ The user does not have the required authorization

166 In the case of a function, Identify the item that is not a valid interface element

---

- ✓ Source Code
- Tables
- Import parameters
- Exceptions
- Export parameters

167 What are field symbols used for

---

- for referencing multiple fields at the same time
- for graphic symbols on screens and lists
- for re-assigning field types
- ✓ for referencing an address of a field

168 Mark the default size for a packed field

---

- ✓ 2
- 8
- size must be specified
- 1
- 4

169 Refer to the following Code. What is the value of sy-fdpos and sy-subrc after the search is executed

---

```
Data: mystring type c value 'SAPDOMAIN'.
```

```
Search mystring for 'X'
```

sy-fdpos = 4 and sy-subrc = 4  
sy-fdpos = 0 and sy-subrc = 0  
sy-fdpos = 4 and sy-subrc = 0  
sy-fdpos = 0 and sy-subrc = 4



170

A Table passed to a function module can be passed in what manner

---

By Exception  
By Value  
By Header Line  
By Table



## TAW10 - Week 1

171 You are in screen painter. What is a requirement when assigning program fields to the screen

---

- data objects must be activated in the dictionary
- the data objects must be activated
- the fields attributes have to be manually defined in the screen painter
- ✓ the program must be activated

172 Which fields are used for sorting the internal table itab in the following code

---

```
Types: begin of itab_structure,
       Field1 type p,
       Field2 type c,
       Field3 type I,
       Field4 type n,
       end of itab_structure.
```

```
Data: itab type table of itab_structure.
```

```
Sort itab.
```

- Field2
- Field1, Field3
- ✓ Field2, Field4
- Field1

173 What is the default length for Integer Data Types

---

- 1
- 2
- size must be specified
- ✓ 4

174 How much memory is reserved for the data object input\_record in the following statement.

---

## TAW10 - Week 1

```
Types: begin of rec_type,  
       flag      type c,  
       count(3) type c,  
       today     type d,  
       end of rec_type.
```

Data: input\_record type rec\_type.

- 5 bytes
- 4 bytes
- ✓ 12 bytes
- 0 bytes

175 An Authorization Object can contain how many authorization fields

---

- ✓ 10
- unlimited
- 0
- defined by Basis

176 Which is NOT a valid TYPE definition

---

**(More than one answer is correct)**

- ✓ Types: t\_mytab type lfa1 of standard table.
- ✓ Type: t\_mytab type lfa1.
- Types: t\_mytab type lfa1.
- Types: t\_mytab like lfa1.

177 What is true about PARAMETER objects in ABAP.

---

- Parameter objects are a maximum of 30 characters in length
- Lower Case is the default
- ✓ You can use text elements with parameters

178 Select the one item that is not a SAP Default Navigation Button on a standard list

---

- ✓ Save
- Cut/Paste
- Find
- Back/Exit/Cancel

179 What does a context object provide

---

**(More than one answer is correct)**

- Object oriented Programming
- Increased Database Load
- ✓ Reuseability
- Stored calculated values on the presentation server
- ✓ Smaller and simpler Programs

180 What is the value of result after the following code is executed.  
Assume that the user default is set to Fixed Point Arithmetic

---

```
DATA: result TYPE p DECIMALS 2.
```

```
Result = '3000.00' * '0.30'.
```

- result = 900.0000
- result = 90000.00
- result = 9000000
- ✓ result = 900.00

TAW10 - Week 1

181 What are field symbols used for

---

- ✓ for referencing an address of a field
- for re-assigning field types
- for referencing multiple fields at the same time
- for graphic symbols on screens and lists

182 What does workflow achieve

---

**(More than one answer is correct)**

- ✓ builds screen sequences
- ✓ controls information flow
- manages communication media
- ✓ automates execution of activities

183 When creating a function using the function builder, you can set the attribute of the function to determine its processing type. What are the available processing types.

---

**(More than one answer is correct)**

- ✓ Enabled
- ✓ Normal
- ✓ Update
- Non Updateable
- ✓ Remote-enabled

184 Name the layers of the R/3 architecture.

---

**(More than one answer is correct)**

- ✓ Application
- Communication
- Internet

- ✓ Database
- ✓ Presentation

185 Refer to the following code. What is required to successfully access the individual structure fields in the FORM

---

```
Data: st_mytab like mytab.
Perform write_lines using st_mytab.
Form write_lines using rec.
  Write: / rec-field1, rec-field2.
Endform.
```

- ✓ Rec needs to be defined globally as a DATA object
- ✓ The formal parameter 'rec' should be referenced by value
- Rec needs to be defined LIKE mytab in the FORM
- The prefix REC is not needed

186 What should be performed after an R3 upgrade

---

- ✓ Run SPAU to adjust change requests
- Run RDDMASG0
- Release all Change Requests
- Run SPDD to adjust dictionary objects

187 Select the one item that is not a SAP Default Navigation Button on a standard list

---

- ✓ Back/Exit/Cancel
- Find
- Cut/Paste
- Save

188 What statement will clear the entire contents of the internal table itab that has no header line.

---

```
Types: begin of itab_structure,
       Field1 type p,
       Field2 type c,
       Field3 type I,
       Field4 type n,
       end of itab_structure.
```



## TAW10 - Week 1

Data: itab type standard table of itab\_structure.

Data: wa\_itab type itab\_structure.

- ✓ Initialize itab
- Initialize wa\_itab
- ✓ Clear itab
- Clear wa\_itab

189 Processing Blocks in an ABAP program can best be defined as

---

- Processing units that execute based on their position in the source code
- An active section of program code
- ✓ Processing areas for the Global Data of a program
- Smallest units in ABAP

190 What must be assigned to search help parameters

---

- ✓ data element
- domain
- nothing
- values

TAW10 - Week 1

191 What has happened if an authorization fails with sy-subrc = 4

---

- The authorization check used the incorrect authorization object
- The user has an authorization containing the required values
- The user does not have the required authorization

192 What is true about PARAMETER objects in ABAP.

---

- You can use text elements with parameters
- Parameter objects are a maximum of 30 characters in length
- Lower Case is the default

193 In the Catch statement, What is every runtime error assigned to

---

- Catch Class
- Development Class
- Case
- Error Class

194 Which tool is used to manage and organize development objects

---

- Customizing Organizer
- Repository Browser
- Information System
- WorkBench Organizer

195 What menu options are available on all screens.

---

**(More than one answer is correct)**

- ✓ Tools
- ✓ System
- Options
- Status
- ✓ Help

196 Which addition to the Parameters statement is not valid

---

- ✓ Value
- Type
- Default
- Like

197 What is the structure of the internal table when a select-options is declared in your program.

---

- High Low Sign Operator
- Sign Operator High Low
- Low High Sign Option
- ✓ Sign Option Low High

198 Static data records that have a long life are considered to be:

---

- Customer documents
- Client data
- Transactional data
- ✓ Master Data

199 Which statements would bypass current loop processing in the DO LOOP and continue processing with the next loop pass.

---

```
Report ABC.  
Data:  
Start-of-Selection.  
Perform Form A.  
End-of-Selection.  
Form A.  
Do 10 Times.
```

```
A = A + 1.  
.  
Enddo.  
Endform.
```

**(More than one answer is correct)**

- ✓ CHECK with a false expression
- EXIT
- Reject
- ✓ Continue

200 What interface parameter would you check to determine the success of a BAPI call

---

- ✓ Exceptions Parameter 'RETURN'
- Export Parameter 'RETURN'
- Dictionary Structure BAPIRET2
- Export Parameter 'sy-subrc'

## TAW10 - Week 1

201 Select the one item that is not a SAP Default Navigation Button on a standard list

---

- ✓ Back/Exit/Cancel
- Save
- ✓ Cut/Paste
- Find

202 Refer to the following code and indicate which statements are true

---

```
Data: cl_container type ref to cl_gui_custom_container,
      cl_grid      type ref to cl_gui_alv_grid.
```

**(More than one answer is correct)**

- ✓ cl\_container points to the object that communicates with the ALV grid control
- ✓ cl\_grid points to the object that communicates with the ALV grid control
- cl\_grid points to the object that communicates with the container control
- ✓ cl\_container points to the object that communicates with the container control

203 What does the following statement mean Write 'Hello'(001)

---

```
Write 'Hello' (001)
```

- ✓ If Text Element 001 is not in your login language, then 'Hello' is displayed
- Add the variable 'Hello' to message 001
- This is not a valid statement
- Write out 'Hello' and the contents of text element 001

204 What does SAPNET not provide

---

- ✓ Look for training courses
- Connect to other SAP sites
- Seek Problem resolution

Search the Note database

205 What is the role of the dispatcher

---

- ✓ Manages services between R/3 systems
- Controls resources for the R/3 applications
- Issues SQL requests to the underlying database
- Dispatches tasks to non R3 systems

206 Where does information come from when you press F1 on a screen field

---

- ✓ Data element documentation
- Search help
- Domain short text
- Domain Help values

207 An Authorization Object can contain how many authorization fields

---

- ✓ 10
- 0
- defined by Basis
- unlimited

208 What is the value of result after the following code is executed.  
Assume that the user default is set to Fixed Point Arithmetic

---

```
DATA: result TYPE p DECIMALS 2.
```

```
Result = '3000.00' * '0.30'.
```

- result = 9000000
- result = 900.0000
- result = 90000.00
- ✓ result = 900.00

209 What is the result of the following code. Assume there are 5 records in itab.

---

```
Loop at itab.  
  ctr = ctr + 1  
  write: sy-tabix.  
  check ctr = 3.  
  delete itab  
endloop.
```

✓

```
1 2 3 3 4  
1 2 3 4 5  
1 2 3 4  
1 2 4 5
```

210 What can occur if a conversion rule does not exist for fields of incompatible data types

---

**(More than one answer is correct)**

- ✓ A run time error for statically defined fields
- ✓ A syntax error for dynamically defined fields
- ✓ A syntax error for statically defined fields
- ✓ A run time error for dynamically defined fields

TAW10 - Week 1

211 Where does information come from when you press F1 on a screen field

---

- ✓ Data element documentation
- Domain short text
- Domain Help values
- Search help

212 Which software component in the work process is responsible for controlling commits and rollbacks

---

- Dialog Processor
- ABAP Processor
- ✓ Database Interface
- Screen Processor

213 Select the valid types of user dialogs

---

**(More than one answer is correct)**

- ✓ Business Objects
- ✓ Screens
- ✓ Selection Screen
- ✓ Lists
- Logical Database

214 What is the effect of a false CHECK statement within a loop

---

- The same processing block is re-executed
- Processing continues with the next processing block
- ✓ Processing resumes at the beginning of the next loop pass
- Processing continues with the next processing block

215 Which fields are used for sorting the internal table itab in the



following code

---

```
Types: begin of itab_structure,
       Field1 type p,
       Field2 type c,
       Field3 type I,
       Field4 type n,
       end of itab_structure.
```

```
Data: itab type table of itab_structure.
```

```
Sort itab.
```

```
Field1
Field1, Field3
Field2
Field2, Field4
```

✓

216 Identify the includes that would get generated if your program name is SAPMZMYPROGRAM

---

```
MZMYPROGRAMDATA
SAPMZMYPROGRAMTOP
MZMYPROGRAMTOP
SAPMZMYPROGRAM
MZMYPROGRAMINCLUDE
```

✓

217 Which part of the internal table syntax determines how abap accesses the rows of the internal table

---

```
uniqueness attribute
table type
line type
key sequence
```

✓

218 Mark the item that is not true about the Catch..EndCatch statement

---

✓

```
a runtime error in a form called within a catch block is caught
the return value assigned to the system exception is stored in sy-subrc
```

## TAW10 - Week 1

a runtime error causes the system to go to the  
ENDCATCH statement  
the Others option catches any runtime errors not already  
assigned

219 What is the value of result after the following code is executed

---

```
DATA: result TYPE I.
```

```
result = 5 / 10.
```

- result = .5
- result = 1
- result = 2
- result = 0

220 How much memory is reserved for the data object input\_record in the following statement.

---

```
Types: begin of rec_type,  
       flag      type c,  
       count(3) type c,  
       today     type d,  
       end of rec_type.
```

```
Data: input_record type rec_type.
```

- 0 bytes
- 5 bytes
- 4 bytes
- 12 bytes

## TAW10 - Week 1

- 221 A Program makes the function call listed below. What takes place if the function raises an exception and the calling program does not list the exception in its call to the function
- 

```
Call Function 'MYFUNCTION'
  exporting
    e1 = p1
  importing
    i1 = p2
```

- Message occurs
- Program is suspended
- Program continues
- ✓ Runtime error

- 222 What are the tasks of the dispatcher.
- 

**(More than one answer is correct)**

- ✓ organizing communication
- ✓ distributing transaction load
- assigning users to work processes
- performing program syntax checks

- 223 Mark the valid use of the data statement. Assume that ZBOOK-ID is a dictionary object
- 

- ✓ Data fielda value zbook-id
- ✓ Data fielda like zbook-id
- Data fielda(5) like zbook-id
- Data fielda type c like zbook-id

- 224 How many dialog steps in an SAP Transaction.
- 

- ✓ One for every explicit database commit
- At least One
- Only One

225 What tasks could be performed in SAPNET

---

**(More than one answer is correct)**

- ✓ Registering developers
- ✓ Registering changes to SAP objects
- Registering changes to customer objects
- Registering customer objects for local development

226 What interface parameter would you check to determine the success of a BAPI call

---

- ✓ Export Parameter 'RETURN'
- Exceptions Parameter 'RETURN'
- Export Parameter 'sy-subrc'
- Dictionary Structure BAPIRET2

227 Identify the standard buffer setting for context objects

---

- ✓ Permanent
- No
- Shared
- Temporary

228 What is the role of the dispatcher

---

- ✓ Dispatches tasks to non R3 systems
- Controls resources for the R/3 applications
- Issues SQL requests to the underlying database
- Manages services between R/3 systems

229 Where does information come from when you press F1 on a screen field

---

Domain Help values  
Domain short text  
Search help  
Data element documentation



230 How could you retrieve a single entry from MYTABLE . (Key fields are number, name)

---



Select single \* from MYTABLE where number = '01' and name = 'LISA'.  
Select \* from MYTABLE where number = '01' and name = 'LISA'.  
Select \* from MYTABLE where number = '01' Endselect.  
Select single \* from MYTABLE with keys

## TAW10 - Week 1

231 What is the effect of a false CHECK statement within a loop

---

- ✓ The same processing block is re-executed
- Processing continues with the next processing block
- Processing continues with the next processing block
- Processing resumes at the beginning of the next loop pass

232 What is written to the report in the following code

---

```
Data: Fielda type i value 1.
Perform Calculate_Sales.
Fielda = fielda + 1.
write:/ fielda.
```

```
Form Calculate_Sales.
  Data: Fielda type I value 2.
  Fielda = Fielda + 2.
Endform.
```

- 4
- 1
- 5
- 3
- ✓ 2

233 Which work process manages SAP locks

---

- dequeue
- authorization management
- ✓ enqueue
- gateway
- dispatcher

234 Which service is responsible for communication between distributed dispatchers

---

communication

✓ dialog  
gateway  
message

235 A Program makes the function call listed below. What takes place if the function raises an exception and the calling program does not list the exception in its call to the function

---

```
Call Function 'MYFUNCTION'
  exporting
    e1 = p1
  importing
    i1 = p2
```

✓ Program continues  
Program is suspended  
Runtime error  
Message occurs

236 Identify the valid statement

---

✓ Constants: C1(4) type C value 'ABCD'.  
Constants: C1(4) type C.  
Constants: C1(4) type C like mytab-booking.  
Constants: C1(4) type D.

237 Identify the valid chaining statement

---

✓ Chain write ctr1 ctr2 ctr3.  
write ctr1: ctr2:ctr3.  
Write: ctr1, ctr2, ctr3.  
write ctr1, ctr2, ctr3.  
write: ctr1 ctr2 ctr3.

238 What is the structure of the internal table when a select-options is declared in your program.

---

✓ Sign Option Low High  
Sign Operator High Low  
High Low Sign Operator

Low High Sign Option

239 Assuming you have created a data object of type c with the name ZFIELDA in your program. Which of the following is allowed

---

- ✓ Types: ZFIELDA type I  
Data: ZFIELDA type n  
Data: ZFIELDA type c  
Constants: ZFIELDA type n

240 What is the value of ZFIELDDB after the last line of the following code is executed

---

```
Data: ZFIELDA(5) type c value 'ABCDE'.  
      ZFIELDDB(4) type c.
```

```
ZFIELDA = XX .  
Clear ZFIELDA.  
ZFIELDDB = ZFIELDA.
```

- ABCDE
- ABCD
- BCDE
- ✓ Spaces



TAW10 - Week 1

241 What is true about trapping errors with the Catch statement

---

- The statement immediately following the CATCH statement is executed in the event of an error trapped by the CATCH statement
- An Endcatch statement is required
- A CASE statement can be used to validate the value of the error class
- A data variable defined with type X must be defined to receive the raised error code

242 What type of SQL is most commonly used in the ABAP language

---

- ISO 900 SQL
- Native SQL
- ANSI SQL
- OPEN SQL

243 Which Basis configuration would typically run on one server

---

- 3 Tier Central
- 2 Tier Presentation Database

244 Where is the name of the currently active gui status stored

---

- In the user context area
- SY-UCOMM
- SY-PFKEY
- SY-STATUS

245 What is the structure of the internal table when a select-options is declared in your program.

- ✓ Low High Sign Option
- High Low Sign Operator
- Sign Operator High Low
- Sign Option Low High

246 Refer to the following code. What is the value of Field1 and Field 2

---

```
SPLIT 'SAPDOMAIN' AT 'DO' INTO FIELD1 FIELD2.
```

- ✓ Field1 contains 'DO', Field2 contains 'DOMAIN'
- Field1 contains 'SAPDO', Field2 contains 'MAIN'
- Field1 contains 'SAP', Field2 contains 'MAIN'

247 Which of the following allocates memory

---

- ✓ Dictionary Type
- Data Type
- Report Statement
- Data Object

248 How could you retrieve a single entry from MYTABLE . (Key fields are number, name)

---

- ✓ Select single \* from MYTABLE with keys
- Select single \* from MYTABLE where number = '01' and name = 'LISA'.
- Select \* from MYTABLE where number = '01' and name = 'LISA'.
- Select \* from MYTABLE where number = '01' Endselect.

249 What is the Effect of not Typing Formal parameters in a Form

---

- ✓ Forms are less flexible and are guaranteed no chance of a run time error
- Conversion never occurs
- No effect

Forms are more flexible but prone to a short dump if  
conversion does not work  
Conversion always occurs

250 Refer to the following code. What is required to successfully access  
the individual structure fields in the FORM

---

```
Data: st_mytab like mytab.  
Perform write_lines using st_mytab.  
Form write_lines using rec.  
  Write: / rec-field1, rec-field2.  
Endform.
```

- ✓ The prefix REC is not needed
- Rec needs to be defined LIKE mytab in the FORM
- Rec needs to be defined globally as a DATA object
- The formal parameter 'rec' should be referenced by value

TAW10 - Week 1

251 What is the default mode for passing actual parameters in a Perform

---

- ✓ By Reference
- By Changing
- By Value

252 What system variable is reset at the exit of a loop of an internal table.  
i.e. Loop at itab. ... Endloop.

---

- ✓ SY-DBCNT
- SY-INDEX
- ✓ SY-TABIX
- SY-LOOP

253 Identify developer tools that are delivered with R/3

---

**(More than one answer is correct)**

- ✓ Customizing
- ✓ CATT
- Dictionary Trace
- ✓ SQL Trace
- ✓ Debugger

254 Identify the standard methods commonly found in BAPI's

---

**(More than one answer is correct)**

- ✓ UPDATEDetail
- ✓ GETLIST
- ✓ CREATEFROMDATA
- CREATelIST
- ✓ GETDETAIL

255 What part of an SAP system is responsible for converting OPEN SQL statements to Native SQL

---

- Database Server
- ABAP Interpreter
- Basis System
- Dispatcher
- ✓ Database Interface

256 What tasks could be performed in SAPNET

---

**(More than one answer is correct)**

- ✓ Registering developers
- ✓ Registering changes to SAP objects
- Registering customer objects for local development
- Registering changes to customer objects

257 Which statements would bypass current loop processing in the DO LOOP and continue processing with the next loop pass.

---

```
Report ABC.  
Data:  
Start-of-Selection.  
Perform Form A.  
End-of-Selection.  
Form A.  
Do 10 Times.  
    A = A + 1.  
    .  
Enddo.  
Endform.
```

**(More than one answer is correct)**

- ✓ CHECK with a false expression
- EXIT
- ✓ Continue
- Reject

258 What program type can be executed directly

---

- ✓ Include
- Class
- Function Group
- Executable

259 In what case would namespaces be practical

---

- ✓ independent 3rd party development projects
- small internal projects
- to uniquely identify each object in a large project

260 What do search statements REPLACE, SHIFT, CONCATENATE, SPLIT have in common

---

**(More than one answer is correct)**

- ✓ They all set sy-fdpos
- ✓ They all treat the operands as type C regardless of their actual type
- ✓ They all distinguish between upper and lower case
- ✓ They all set sy-subrc
- The actual type of each operand determines how the string processing is performed

TAW10 - Week 1

261 Where are authorizations managed for a given user

---

- ✓ In the users own data
- ✓ In the user master record
- ✓ In the tauth table
- ✓ in the USER01 table

262 Mark the item that is not true about the Catch..EndCatch statement

---

- ✓ a runtime error in a form called within a catch block is caught
- ✓ a runtime error causes the system to go to the ENDCATCH statement
- ✓ the return value assigned to the system exception is stored in sy-subrc
- ✓ the Others option catches any runtime errors not already assigned

263 What are the tasks of the dispatcher.

---

**(More than one answer is correct)**

- ✓ distributing transaction load
- ✓ performing program syntax checks
- ✓ assigning users to work processes
- ✓ organizing communication

264 What is true about classes and objects in Object Oriented ABAP

---

**(More than one answer is correct)**

- ✓ Classes are an instance of an object
- ✓ Objects are an instance of a class
- ✓ Objects can change their class
- ✓ Class is a template for an object

265 What is the value of result after the following code is executed

---

```
DATA: result TYPE I.
```

```
result = 5 / 10.
```

- ✓ result = 1
- result = 2
- result = 0
- result = .5

266 What menu options are available on all screens.

---

**(More than one answer is correct)**

- ✓ Help
- Status
- Options
- ✓ System
- Tools

267 Mark the default size for a packed field

---

- ✓ size must be specified
- 8
- 2
- 1
- 4

268 Mark the item that is not a valid work process

---

- Update
- Spool
- ✓ Gateway
- Background

269 In what case would you typically use a NUMC field

---



- ✓ Where only numbers are allowed and there is no need for arithmetic operations
- Where only numbers are allowed and there is a need for arithmetic operations
- Where there is a need for numbers, characters, and arithmetic operations

270 In the case of a function, Identify the item that is not a valid interface element

---

- ✓ Import parameters
- Export parameters
- Source Code
- Exceptions
- Tables

TAW10 - Week 1

271 What determines the sequence in which events blocks are processed

---

- ✓ The Programmer
- The run time system
- The Dispatcher
- The User

272 In what case would namespaces be practical

---

- ✓ small internal projects
- to uniquely identify each object in a large project
- independent 3rd party development projects

273 Which Basis configuration would typically run on one server

---

- ✓ 3 Tier
- Central
- Database
- 2 Tier Presentation

274 What system field would you query to determine the current detail list

---

- ✓ sy-lsind
- sy-list
- sy-field
- sy-listi

275 A Table passed to a function module can be passed in what manner

---

- ✓ By Header Line
- By Value

By Exception  
By Table

276 What is the effect of the EXIT statement in the following code

---

```
Report ABC
Data: ..

Start-of-Selection.
Perform Form A.
End-of-Selection.

Form A.
  Loop at inttab.
    ...
    Exit.
  Endloop.
Endform.
```

- Exits the Program
- Exits the Form
- Exits the Start-of-Selection Event
- ✓ Exits the Loop

277 What is the customer namespace for Functions

---

- F
- Y or Z
- FZ
- ✓ Y\_ or Z\_

278 If you want the debugger to stop when the value of 'fielda' changes.  
Which option would you set in the debugger

---

- Fields
- Object
- ✓ WatchPoint
- Overview

279 How is security handled at the application level

---

The authorization concept is used to restrict access to the dictionary

The authorization concept is used to restrict access to users

The authorization concept is used to restrict access to servers and work processes

✓ The authorization concept is used to restrict access to data and transactions

280

What should be performed after an R3 upgrade

---

Run RDDMASG0

✓ Run SPDD to adjust dictionary objects

Run SPAU to adjust change requests

Release all Change Requests

## TAW10 - Week 1

- 281      How are locks removed from the lock tables
- 
- ✓      The database breaks  
The update task removes them at the end of the SAP LUW  
The update task removes them at the beginning of the SAP LUW  
Commit Work statement is issued
- 282      Identify the valid chaining statement
- 
- ✓      Write: ctr1, ctr2, ctr3.  
Chain write ctr1 ctr2 ctr3.  
write ctr1: ctr2:ctr3.  
write: ctr1 ctr2 ctr3.  
write ctr1, ctr2, ctr3.
- 283      What program type can be executed directly
- 
- ✓      Executable  
Function Group  
Class  
Include
- 284      Assuming you have created a data object of type c with the name ZFIELDA in your program. Which of the following is allowed
- 
- ✓      Data: ZFIELDA type c  
Types: ZFIELDA type I  
Constants: ZFIELDA type n  
Data: ZFIELDA type n
- 285      What is the result of the following date calculation. Assume current date is 20001220

---

Data: Today(8) type C.

Today = sy-datum.

Today = 10.

20001220

10001220

20011210

✓ 10

286 Structure MY\_STRUCTURE is created in the dictionary. When does the structure get created in the underlying database

---

When the database administrator physically creates the table

✓ It does not correspond to an object in the underlying database and does not get created

When the table is activated

At the end of the table creation after it is saved.

At the beginning of the table creation

287 What is true about an Authorization

---

**(More than one answer is correct)**

✓ Defines permissible values for each authorization field listed in the authorization object

An authorization is defined in the program attributes

✓ It is attached to profiles

288 How would you set breakpoints in your program for debugging.

---

**(More than one answer is correct)**

✓ In the program editor, set breakpoint

✓ Put a break-point statement in your program code

Start program in background mode

In Development workbench, set breakpoint

289 What does workflow achieve

---

**(More than one answer is correct)**

- ✓ automates execution of activities
- ✓ builds screen sequences
- ✓ controls information flow
- ✓ manages communication media

290 Identify the standard methods commonly found in BAPI's

---

**(More than one answer is correct)**

- ✓ GETLIST
- ✓ CREATEFROMDATA
- ✓ UPDATEDetail
- ✓ GETDETAIL
- ✓ CREATELIST

## TAW10 - Week 1

291 Identify the characteristics of a BAPI

---

**(More than one answer is correct)**

- ✓ It is an interface
- ✓ Can be a method of an object
- Can only be use inside SAP
- ✓ It is impemented as a function
- It is an Object

292 What is the value of result after the following code is executed.  
Assume that the user default is set to Fixed Point Arithmetic

---

```
DATA: result TYPE p DECIMALS 2.
```

```
Result = '3000.00' * '0.30'.
```

- result = 9000000
- ✓ result = 900.00
- result = 900.0000
- result = 90000.00

293 What is the customer allowed naming convention for lock objects

---

- ✓ EZ\* or EY\*
- ZE\* or YE\*
- Z\* or Y\*
- ENQUEUE\* or DEQUEUE\*

294 What does Compression Mode achieve in the ABAP editor

---

- Reduces the size of the generated load module
- ✓ Hides the code between keywords
- Limits the functionality of runtime analysis to base features
- Provides the ability to powertype key words



295 What is used by Basis to move Repository objects across SAP systems

---

- Customizing Organizer
- WorkBench Organizer
- ✓ Transport System
- Repository Infosys
- ABAP WorkBench

296 What is the value of result after the following code is executed

---

```
DATA: result TYPE I.
```

```
result = 5 / 10.
```

- result = .5
- result = 2
- result = 0
- ✓ result = 1

297 Which Basis configuration would typically run on one server

---

- 2 Tier Presentation
- 3 Tier
- Database
- ✓ Central

298 Mark the valid statement for reading an entry from an internal table of type sorted

---

- ✓ Read Table itab by binary key k1
- Read Table itab with Table Key K1
- Read Table itab by key K1
- Read Table itab with sorted key k1

299 Identify the element that is not part of the user interface

---

application toolbar

- ✓ selection screen
- Function key settings
- standard toolbar
- menu bar
- title bar

300 What is true about an Authorization

---

**(More than one answer is correct)**

- ✓ It is attached to profiles
- ✓ Defines permissible values for each authorization field listed in the authorization object
- An authorization is defined in the program attributes

## TAW10 - Week 1

- 301      Where are the entries for transportable repository objects stored
- 
- ✓            In the repository  
              TADIR  
              TSTC  
              TRDIR
- 302      What has happened if an authorization fails with sy-subrc = 4
- 
- ✓            The user does not have the required authorization  
              The user has an authorization containing the required  
              values  
              The authorization check used the incorrect authorization  
              object
- 303      What method of Class CL\_GUI\_ALV\_GRID would be used to display  
           the contents of an internal table
- 
- ✓            SET\_TABLE\_FOR\_DISPLAY  
              SET\_TABLE\_FOR\_FIRST\_DISPLAY  
              REFRESH\_TABLE\_DISPLAY  
              CONSTRUCTOR
- 304      Identify the valid statement
- 
- Constants: C1(4) type C.  
              Constants: C1(4) type D.  
✓            Constants: C1(4) type C value 'ABCD'.  
              Constants: C1(4) type C like mytab-booking.
- 305      Mark the default size for a packed field
-

- ✓ 4  
8  
1  
2  
size must be specified
- 306 Which software component in the work process is responsible for controlling commits and rollbacks
- 
- ✓ Dialog Processor  
ABAP Processor  
Database Interface  
Screen Processor
- 307 How would you clear the body of an internal table (with a header line).
- 
- (More than one answer is correct)**
- ✓ Refresh ITAB []  
Clear ITAB[]  
Clear ITAB  
✓ Refresh ITAB
- 308 What is a valid configuration for an R3 System.
- 
- (More than one answer is correct)**
- ✓ No Application server and one Database server  
One Application server and many Database servers  
Many Application servers and one Database server  
One Application server and one Database server
- 309 What is used by Basis to move Repository objects across SAP systems
- 
- ✓ Transport System  
ABAP WorkBench  
WorkBench Organizer

Repository Infosys  
Customizing Organizer

310 An Authorization Object can contain how many authorization fields

- 0
- defined by Basis
- unlimited
- 10



## TAW10 - Week 1

311 Which addition to the Parameters statement is not valid

---

- ✓ Like
- Default
- Value
- Type

312 Mark the default size for a packed field

---

- 1
- size must be specified
- 2
- ✓ 8
- 4

313 Refer to the following code and indicate which statements are true

---

```
Data: cl_container type ref to cl_gui_custom_container,
      cl_grid      type ref to cl_gui_alv_grid.
```

**(More than one answer is correct)**

- ✓ cl\_grid points to the object that communicates with the container control
- ✓ cl\_grid points to the object that communicates with the ALV grid control
- ✓ cl\_container points to the object that communicates with the container control
- cl\_container points to the object that communicates with the ALV grid control

314 Which service is responsible for communication between distributed dispatchers

---

- ✓ message
- communication
- dialog

gateway

315 Which software component in the work process is responsible for controlling commits and rollbacks

---

- ✓ ABAP Processor
- Screen Processor
- Dialog Processor
- Database Interface

316 Standard and sorted tables are referred to as

---

- ✓ generic
- index
- non unique
- keyed
- Unique

317 How would you clear the body of an internal table (with a header line).

---

**(More than one answer is correct)**

- ✓ Clear ITAB
- ✓ Clear ITAB[]
- Refresh ITAB
- Refresh ITAB []

318 Which field gets set in the calling program if an exception occurs in a function module

---

- exception integers
- interface parameters
- exception parameters
- ✓ sy-subrc

319 What system parameter is responsible for setting the time-out on a long running dialog transaction

✓  
rdisp/max\_wprun\_time  
rdisp/btctime  
rdisp/txntime

320 What is the customer namespace for Functions

---

✓  
FZ  
Y\_ or Z\_  
F  
Y or Z



TAW10 - Week 1

321 What tool is used to define flow logic

---

- ✓ ABAP Editor
- Screen Painter
- Flow Logic Editor
- Function Builder

322 What is the system variable for determining how many database operations were performed

---

- ✓ sy-tabix
- sy-subrc
- sy-dbcnt
- sy-index

323 What interface parameter would you check to determine the success of a BAPI call

---

- Export Parameter 'sy-subrc'
- Dictionary Structure BAPIRET2
- Exceptions Parameter 'RETURN'
- ✓ Export Parameter 'RETURN'

324 What is true about classes and objects in Object Oriented ABAP

---

**(More than one answer is correct)**

- ✓ Objects are an instance of a class
- ✓ Class is a template for an object
- Classes are an instance of an object
- Objects can change their class

325 Identify the characteristics of a Business Object

**(More than one answer is correct)**

- ✓ Business objects are business oriented
- ✓ Business objects provide methods to implement business functions
- ✓ Business objects are managed in the Business Object Repository (BOR)  
Business objects ONLY use BAPI's to access data  
Business objects require knowledge of the internal source code to be able to access the data

326 What must be assigned to search help parameters

---

- domain
- values
- nothing
- ✓ data element

327 Where are local data types defined

---

- ABAP Workbench
- Repository
- ✓ in ABAP Programs
- Dictionary

328 What clause on the Select statement is used to invoke authorization checking

---

- CHECK
- User Master Record
- Authority-check
- ✓ It is not possible

329 Processing Blocks in an ABAP program can best be defined as

---

TAW10 - Week 1

- An active section of program code
- Processing areas for the Global Data of a program
- Processing units that execute based on their position in the source code
- ✓ Smallest units in ABAP

330 Identify developer tools that are delivered with R/3

---

**(More than one answer is correct)**

- ✓ Debugger
- ✓ SQL Trace
- Dictionary Trace
- Customizing
- ✓ CATT

## TAW10 - Week 1

331 What can occur if a conversion rule does not exist for fields of incompatible data types

---

**(More than one answer is correct)**

- A syntax error for dynamically defined fields
- A run time error for statically defined fields
- A run time error for dynamically defined fields
- A syntax error for statically defined fields

332 Standard and sorted tables are referred to as

---

- index
- non unique
- keyed
- generic
- Unique

333 Mark the valid statement for reading an entry from an internal table of type sorted

---

- Read Table itab with sorted key k1
- Read Table itab by key K1
- Read Table itab with Table Key K1
- Read Table itab by binary key k1

334 How would you set breakpoints in your program for debugging.

---

**(More than one answer is correct)**

- Start program in background mode
- Put a break-point statement in your program code
- In Development workbench, set breakpoint
- In the program editor, set breakpoint

335 Mark the item that is not true about the Catch..EndCatch statement

---

- the return value assigned to the system exception is stored in sy-subrc
- the Others option catches any runtime errors not already assigned
- ✓ a runtime error in a form called within a catch block is caught
- a runtime error causes the system to go to the ENDCATCH statement

336 What will be written to the list in the following code. Assume all defaults are taken when the function was defined.

---

```
Data: fielda(4) type c.
      fielda = AAAA .
```

```
Call Function Z_TEST_FUNCTION
Exporting f_fielda = fielda.
```

```
Write fielda.
```

```
Function Z_TEST_FUNCTION
Importing f_fielda
Exporting f_fieldb
```

```
f_fielda = BBBB .
f_fieldb = CCCC
```

- ✓ CCCC
- BBBB
- AAAA

337 What is the effect of sorting a sorted internal table

---

- ✓ Syntax error
- Program abend
- Breaks the sort sequence
- Uses linear search rather than binary

338 What event is used to create detail lists

---

- ✓ Initialization
- New-Page
- Suppress Dialog
- At Line-Selection
- On Detail

339 What is the default length for Integer Data Types

---

- 2
- 1
- ✓ 4
- size must be specified

340 An Authorization refers to how many Authorization Objects

---

- 0
- unlimited
- 10
- ✓ 1
- defined by Basis

## TAW10 - Week 1

341 How many servers in a 3 tier R/3 system

---

- Only 3
- 3 for each tier
- 1
- ✓ At least 3

342 What are the tasks of the dispatcher.

---

**(More than one answer is correct)**

- ✓ performing program syntax checks
- ✓ organizing communication
- ✓ assigning users to work processes
- ✓ distributing transaction load

343 What programming language is used to develop the business applications.

---

- ✓ ABAP
- C
- VB
- C++
- Cobol

344 What is the result of the following code. Assume there are 5 records in itab.

---

```

Loop at itab.
  ctr = ctr + 1
  write: sy-tabix.
  check ctr = 3.
  delete itab
endloop.

```

1 2 3 4  
1 2 4 5

✓ 1 2 3 3 4  
1 2 3 4 5

345 What is a client in an R/3 system

---

Delivered by Sap  
Vendor  
✓ Organizational unit  
Customer

346 Which statements would bypass current loop processing in the DO LOOP and continue processing with the next loop pass.

---

```
Report ABC.
Data:
Start-of-Selection.
Perform Form A.
End-of-Selection.
Form A.
Do 10 Times.
    A = A + 1.
    .
Enddo.
Endform.
```

**(More than one answer is correct)**

✓ Continue  
✓ CHECK with a false expression  
Reject  
EXIT

347 Refer to the following code. What is the value of Field1 and Field 2

---

```
SPLIT 'SAPDOMAIN' AT 'DO' INTO FIELD1 FIELD2.
```

Field1 contains 'SAPDO', Field2 contains 'MAIN'  
Field1 contains 'DO', Field2 contains 'DOMAIN'  
✓ Field1 contains 'SAP', Field2 contains 'MAIN'

348 What can occur if a conversion rule does not exist for fields of incompatible data types

---



**(More than one answer is correct)**

- ✓ A syntax error for statically defined fields
- A run time error for statically defined fields
- A syntax error for dynamically defined fields
- ✓ A run time error for dynamically defined fields

349 What statement is used in ABAP programming to check if a user is authorized to perform an action

---

- Check sy-subrc
- Check Permission
- ✓ Authority-Check
- Check Authority

350 What does SAPNET not provide

---

- Seek Problem resolution
- Look for training courses
- Search the Note database
- ✓ Connect to other SAP sites

TAW10 - Week 1

351 What can occur if a conversion rule does not exist for fields of incompatible data types

---

**(More than one answer is correct)**

- ✓ A syntax error for dynamically defined fields
- ✓ A run time error for dynamically defined fields
- ✓ A run time error for statically defined fields
- ✓ A syntax error for statically defined fields

352 What statement is used to move identically named fields between structures

---

- ✓ MOVE
- MOVE\_CORRESPONDING
- MOVE-CORRESPONDING
- ASSIGN

353 Where are local data types defined

---

- ✓ Dictionary
- in ABAP Programs
- ABAP Workbench
- Repository

354 Which software component in the work process is responsible for controlling commits and rollbacks

---

- ✓ Database Interface
- ABAP Processor
- Screen Processor
- Dialog Processor

355 How many column headers are displayed on the screen in a standard

list

- 
- 4  
 2  
 1  
 There are no column headers

356 Static data records that have a long life are considered to be:

---

- Master Data  
 Transactional data  
 Client data  
 Customer documents

357 Which is not a valid R3 configuration

---

- Two tier client server  
 Three Tier  
 Single Database  
 Central

358 Refer to the following code. What is required to successfully access the individual structure fields in the FORM

---

```
Data: st_mytab like mytab.
Perform write_lines using st_mytab.
Form write_lines using rec.
  Write: / rec-field1, rec-field2.
Endform.
```

- The formal parameter 'rec' should be referenced by value  
 Rec needs to be defined LIKE mytab in the FORM  
 Rec needs to be defined globally as a DATA object  
 The prefix REC is not needed

359 What statement will clear the entire contents of the internal table itab that has no header line.

---

```
Types: begin of itab_structure,
       field1 type p,
```

## TAW10 - Week 1

```
Field2 type c,  
Field3 type I,  
Field4 type n,  
end of itab_structure.
```

Data: itab type standard table of itab\_structure.

Data: wa\_itab type itab\_structure.

- ✓ Clear itab
- Clear wa\_itab
- Initialize itab
- Initialize wa\_itab

360 What is the role of the dispatcher

---

- ✓ Controls resources for the R/3 applications
- Issues SQL requests to the underlying database
- Manages services between R/3 systems
- Dispatches tasks to non R3 systems

## TAW10 - Week 1

361 How could you retrieve a single entry from MYTABLE . (Key fields are number, name)

---

- ✓ Select \* from MYTABLE where number = '01' and name = 'LISA'.
- ✓ Select \* from MYTABLE where number = '01' Endselect.
- ✓ Select single \* from MYTABLE where number = '01' and name = 'LISA'.
- ✓ Select single \* from MYTABLE with keys

362 What programming language is used to develop the business applications.

---

- ✓ ABAP
- ✓ C++
- ✓ Cobol
- ✓ VB
- ✓ C

363 Identify developer tools that are delivered with R/3

---

**(More than one answer is correct)**

- ✓ Debugger
- ✓ SQL Trace
- ✓ Dictionary Trace
- ✓ Customizing
- ✓ CATT

364 What statement will clear the entire contents of the internal table itab that has no header line.

---

```
Types: begin of itab_structure,
       Field1 type p,
       Field2 type c,
       Field3 type I,
       Field4 type n,
```

```
end of itab_structure.
```

```
Data: itab type standard table of itab_structure.
```

```
Data: wa_itab type itab_structure.
```

- Initialize wa\_itab
- Initialize itab
- ✓ Clear itab
- Clear wa\_itab

365 What determines the sequence in which events blocks are processed

- ✓ The run time system
- The Dispatcher
- The User
- The Programmer

366 In the Catch statement, What is every runtime error assigned to

- Catch Class
- Case
- Development Class
- ✓ Error Class

367 What is the default mode for passing actual parameters in a Perform

- ✓ By Reference
- By Value
- By Changing

368 Where is the record inserted in the internal table itab.

```
Types: begin of itab_structure,  
       Field1 type p,  
       Field2 type c,  
       Field3 type I,  
       Field4 type n,  
end of itab_structure.
```

```
Data: itab type standard table of itab_structure.
```

## TAW10 - Week 1

Data: wa\_itab type itab\_structure.

Insert wa\_itab into table itab.

- ✓ At the beginning
- At the end
- It can't be done
- in the correct sorted position

369 Identify the valid chaining statement

---

- write: ctr1 ctr2 ctr3.
- write ctr1: ctr2:ctr3.
- Chain write ctr1 ctr2 ctr3.
- write ctr1, ctr2, ctr3.
- ✓ Write: ctr1, ctr2, ctr3.

370 Identify the processing blocks of an ABAP program

---

**(More than one answer is correct)**

- ✓ Dialog Module
- Declarations
- Function
- ✓ Event

## TAW10 - Week 1

371 An ABAP program makes calls to function modules from the same function group. What happens with the Global data from the function group

---

**(More than one answer is correct)**

- The global data remains active for the duration of the function call only
- Function modules from the same function group can access the global data when they are called
- The global data remains available for the duration of the calling program
- The global data is reinitialized for each new call

372 Refer to the following code. What is the value of Field1 and Field 2

---

```
SPLIT 'SAPDOMAIN' AT 'DO' INTO FIELD1 FIELD2.
```

- Field1 contains 'DO', Field2 contains 'DOMAIN'
- Field1 contains 'SAPDO', Field2 contains 'MAIN'
- Field1 contains 'SAP', Field2 contains 'MAIN'

373 What are the differences between Parameters and Select-Options in a selection screen

---

**(More than one answer is correct)**

- Parameters create a single field, Select-options create multiple fields
- Select-options create a single field, Parameters create multiple fields
- Select-options use the FOR statement, Parameters use the Type statement
- Parameters use the FOR statement, Select-Options use the Type statement

374 Which fields are used for sorting the internal table itab in the following code

---



## TAW10 - Week 1

```
Types: begin of itab_structure,  
        Field1 type p,  
        Field2 type c,  
        Field3 type I,  
        Field4 type n,  
end of itab_structure.
```

Data: itab type table of itab\_structure.

Sort itab.

✓       Field2, Field4  
          Field2  
          Field1  
          Field1, Field3

375       What system variable is reset at the exit of a loop of an internal table.  
          i.e. Loop at itab. ... Endloop.

---

          SY-DBCNT  
          SY-INDEX  
          SY-LOOP  
✓        SY-TABIX

376       How is security handled at the application level

---

          The authorization concept is used to restrict access to  
          servers and work processes  
          The authorization concept is used to restrict access to users  
✓        The authorization concept is used to restrict access to data  
          and transactions  
          The authorization concept is used to restrict access to the  
          dictionary

377       What are field symbols used for

---

✓        for referencing an address of a field  
          for graphic symbols on screens and lists  
          for referencing multiple fields at the same time  
          for re-assigning field types

378 Which Basis configuration would typically run on one server

---

- ✓ Central  
Database  
3 Tier  
2 Tier Presentation

379 What interface parameter would you check to determine the success of a BAPI call

---

- ✓ Export Parameter 'RETURN'  
Dictionary Structure BAPIRET2  
Exceptions Parameter 'RETURN'  
Export Parameter 'sy-subrc'

380 What system parameter is responsible for setting the time-out on a long running dialog transaction

---

- ✓ rdisp/max\_wprun\_time  
rdisp/btctime  
rdisp/txntime

## TAW10 - Week 1

381 Structure MY\_STRUCTURE is created in the dictionary. When does the structure get created in the underlying database

---

- ✓ It does not correspond to an object in the underlying database and does not get created
- When the table is activated
- When the database administrator physically creates the table
- At the beginning of the table creation
- At the end of the table creation after it is saved.

382 In what case would you typically use a NUMC field

---

- Where there is a need for numbers, characters, and arithmetic operations
- ✓ Where only numbers are allowed and there is no need for arithmetic operations
- Where only numbers are allowed and there is a need for arithmetic operations

383 How could you retrieve a single entry from MYTABLE . (Key fields are number, name)

---

- Select \* from MYTABLE where number = '01' Endselect.
- Select single \* from MYTABLE with keys
- Select \* from MYTABLE where number = '01' and name = 'LISA'.
- ✓ Select single \* from MYTABLE where number = '01' and name = 'LISA'.

384 Identify the one item that is not an ABAP Workbench tool

---

- Function Builder
- ✓ CCMS
- Menu Painter

Screen Painter

385 What is a valid configuration for an R3 System.

---

**(More than one answer is correct)**

- ✓ Many Application servers and one Database server
- No Application server and one Database server
- ✓ One Application server and one Database server
- One Application server and many Database servers

386 How would you determine the program name currently being executed

---

- F9
- F4
- ✓ Use menu option System>Status
- Look in the dictionary

387 Where does information come from when you press F1 on a screen field

---

- Domain Help values
- Domain short text
- ✓ Data element documentation
- Search help

388 What is the Effect of not Typing Formal parameters in a Form

---

- No effect
- Forms are less flexible and are guaranteed no chance of a run time error
- ✓ Forms are more flexible but prone to a short dump if conversion does not work
- Conversion never occurs
- Conversion always occurs

389 Mark the valid use of the data statement. Assume that ZBOOK-ID is a

dictionary object

---

- ✓ Data fielda(5) like zbook-id
- Data fielda like zbook-id
- Data fielda type c like zbook-id
- Data fielda value zbook-id

390 What transaction is used to handle termination updates

---

- SM12
- SE80
- CCMS
- ✓ SM13

## TAW10 - Week 1

391 How many column headers are displayed on the screen in a standard list

---

- ✓ There are no column headers
- 2
- 1
- 4

392 What do search statements REPLACE, SHIFT, CONCATENATE, SPLIT have in common

---

**(More than one answer is correct)**

- ✓ The actual type of each operand determines how the string processing is performed
- ✓ They all distinguish between upper and lower case
- ✓ They all treat the operands as type C regardless of their actual type
- ✓ They all set sy-subrc
- They all set sy-fdpos

393 Structure MY\_STRUCTURE is created in the dictionary. When does the structure get created in the underlying database

---

- At the beginning of the table creation
- At the end of the table creation after it is saved.
- When the table is activated
- When the database administrator physically creates the table
- ✓ It does not correspond to an object in the underlying database and does not get created

394 When does an object get generated

---

When a method of an object is called

TAW10 - Week 1

- ✓ When a CREATE OBJECT statement is processed
- When the program is loaded
- When the reference variable for the class is defined

395 What is the icon that represents a breakpoint

---

- info sign
- warning sign
- ✓ stop sign
- highlighted line

396 What is true about an Authorization Object ?

---

- Authorization Objects contain permissible values for the fields
- Groups up to 10 authorization fields in an OR relationship
- ✓ Groups up to 10 authorization fields in an AND relationship

397 What does the following statement mean Write 'Hello'(001)

---

Write 'Hello' (001)

- ✓ If Text Element 001 is not in your login language, then 'Hello' is displayed
- Write out 'Hello' and the contents of text element 001
- Add the variable 'Hello' to message 001
- This is not a valid statement

398 Identify the servers of which only one can exist in an R/3 system.

---

**(More than one answer is correct)**

- ✓ One application server
- ✓ One message server
- ✓ One database server
- One presentation server
- ✓ One enqueue server

399 What is true about PARAMETER objects in ABAP.

---

- ✓ You can use text elements with parameters  
Parameter objects are a maximum of 30 characters in length  
Lower Case is the default

400 What statement will clear the entire contents of the internal table itab that has no header line.

---

```
Types: begin of itab_structure,  
       Field1 type p,  
       Field2 type c,  
       Field3 type I,  
       Field4 type n,  
       end of itab_structure.
```

```
Data: itab type standard table of itab_structure.
```

```
Data: wa_itab type itab_structure.
```

- ✓ Initialize itab  
Clear wa\_itab  
Clear itab  
Initialize wa\_itab



TAW10 - Week 1

401 What is the default length for Integer Data Types

---

- ✓ size must be specified
- 4
- 1
- 2

402 How would you determine the program name currently being executed

---

- ✓ F9
- Use menu option System>Status
- F4
- Look in the dictionary

403 Identify the internal table types.

---

**(More than one answer is correct)**

- ✓ Standard
- ✓ Hashed
- Key
- Indented
- ✓ Sorted

404 What is true about an Authorization Object ?

---

- ✓ Groups up to 10 authorization fields in an AND relationship
- Authorization Objects contain permissible values for the fields
- Groups up to 10 authorization fields in an OR relationship

405 Which is not a type of RFC call

- ✓ Remote
- Asynchronous
- Transactional
- Synchronous

406 Which statement is valid for processing internal table itab.Data: itab type table of zmytab with header line.

---

- Loop at itab.Endtab.
- Loop where itab-id = A .Endloop.
- Loop at itab where itab-id = A .Endloop.
- ✓ Loop at itab where id = A .Endloop.

407 What is the value of result after the following code is executed

---

```
DATA: result TYPE I.
```

```
result = 5 / 10.
```

- result = 0
- result = .5
- ✓ result = 1
- result = 2

408 What statement is used to move identically named fields between structures

---

- ASSIGN
- MOVE\_CORRESPONDING
- MOVE
- ✓ MOVE-CORRESPONDING

409 What do search statements REPLACE, SHIFT, CONCATENATE, SPLIT have in common

---

**(More than one answer is correct)**

## TAW10 - Week 1

- ✓ They all distinguish between upper and lower case
- They all set sy-fdpos
- ✓ They all set sy-subrc
- ✓ They all treat the operands as type C regardless of their actual type
- The actual type of each operand determines how the string processing is performed

410 Where is the name of the currently active gui status stored

---

- ✓ SY-UCOMM
- SY-PFKEY
- SY-STATUS
- In the user context area

TAW10 - Week 1

411 A Table passed to a function module can be passed in what manner

---

- By Table
- By Exception
- ✓ By Value
- By Header Line

412 What determines the sequence in which events blocks are processed

---

- The User
- The Programmer
- ✓ The run time system
- The Dispatcher

413 Which Basis configuration would typically run on one server

---

- 3 Tier
- 2 Tier Presentation
- Database
- ✓ Central

414 Where is the statement

---

- In a PAI Module
- Anywhere in the program
- ✓ In a Function
- In a Form Only

415 What requirement exists if a field is defined in the dictionary of type CURR

---

- ✓ No other requirement exists
- Decimals must be defined in the domain
- ✓ The field must be linked to another field of type CUKY
- The field must be numeric

416 Which is NOT a valid TYPE definition

---

**(More than one answer is correct)**

- ✓ Types: t\_mytab type lfa1.
- ✓ Types: t\_mytab type lfa1 of standard table.
- ✓ Type: t\_mytab type lfa1.
- Types: t\_mytab like lfa1.

417 Which use of the FORM statement works successfully when passing IT to FORMA

---

```
Types: Begin of line,
      ...
      End of Line.
Types IT_LINE Type Standard table of line.
Data IT TYPE IT_LINE.
Perform FORMA using IT
```

- ✓ FORM FORMA Using P\_IT like LINE
- FORM FORMA Using P\_IT type IT\_LINE
- FORM FORMA Using P\_IT like LINE
- FORM FORMA Using P\_IT like IT\_LINE

418 What is true about trapping errors with the Catch statement

---

- The statement immediately following the CATCH statement is executed in the event of an error trapped by the CATCH statement
- A CASE statement can be used to validate the value of the error class
- ✓ An Endcatch statement is required
- A data variable defined with type X must be defined to receive the raised error code

419 What is the value of result after the following code is executed.  
Assume that the user default is set to Fixed Point Arithmetic

DATA: result TYPE p DECIMALS 2.

Result = '3000.00' \* '0.30'.

- result = 90000.00
- result = 900.0000
- ✓ result = 900.00
- result = 9000000

420 What does the following statement mean Write 'Hello'(001)

---

Write 'Hello' (001)

- ✓ If Text Element 001 is not in your login language, then 'Hello' is displayed
- Write out 'Hello' and the contents of text element 001
- This is not a valid statement
- Add the variable 'Hello' to message 001

TAW10 - Week 1

421 What are the tasks of the dispatcher.

---

**(More than one answer is correct)**

- ✓ organizing communication
- assigning users to work processes
- performing program syntax checks
- ✓ distributing transaction load

422 Which tool is used to manage and organize development objects

---

- Repository Browser
- Information System
- Customizing Organizer
- ✓ WorkBench Organizer

423 What is the effect of sorting a sorted internal table

---

- ✓ Program abend
- Syntax error
- Uses linear search rather than binary
- Breaks the sort sequence

424 Identify the element that is not part of the user interface

---

- ✓ selection screen
- standard toolbar
- title bar
- Function key settings
- application toolbar
- menu bar

425 Standard and sorted tables are referred to as

- 
- ✓ keyed
  - index
  - non unique
  - Unique
  - generic

426 Which statement is valid for processing internal table itab.Data: itab type table of zmytab with header line.

---

- ✓ Loop at itab where itab-id = A .Endloop.
- Loop at itab where id = A .Endloop.
- Loop at itab.Endtab.
- Loop where itab-id = A .Endloop.

427 Which fields are used for sorting the internal table itab in the following code

---

```
Types: begin of itab_structure,
        Field1 type p,
        Field2 type c,
        Field3 type I,
        Field4 type n,
        end of itab_structure.
```

```
Data: itab type table of itab_structure.
```

```
Sort itab.
```

- ✓ Field1, Field3
- Field2, Field4
- Field1
- Field2

428 What is the customer allowed naming convention for lock objects

---

- ✓ EZ\* or EY\*
- Z\* or Y\*
- ENQUEUE\* or DEQUEUE\*
- ZE\* or YE\*



- 429 What will be written to the list in the following code. Assume all defaults are taken when the function was defined.
- 

```
Data: fielda(4) type c.  
fielda = AAAA .
```

```
Call Function Z_TEST_FUNCTION  
Exporting f_fielda = fielda.
```

```
Write fielda.
```

```
Function Z_TEST_FUNCTION  
Importing f_fielda  
Exporting f_fieldb
```

```
f_fielda = BBBB .  
f_fieldb = CCCC
```

✓ BBBB  
CCCC  
AAAA

- 430 Identify the includes that would get generated if your program name is SAPMZMYPROGRAM
- 

SAPMZMYPROGRAM  
MZMYPROGRAMINCLUDE  
SAPMZMYPROGRAMTOP  
MZMYPROGRAMDATA  
✓ MZMYPROGRAMTOP

## TAW10 - Week 1

431 How are locks removed from the lock tables

---

- The update task removes them at the beginning of the SAP LUW
- The database breaks
- ✓ The update task removes them at the end of the SAP LUW Commit Work statement is issued

432 Identify developer tools that are delivered with R/3

---

**(More than one answer is correct)**

- Customizing
- Dictionary Trace
- ✓ CATT
- ✓ SQL Trace
- ✓ Debugger

433 Where does information come from when you press F1 on a screen field

---

- Search help
- Domain Help values
- Domain short text
- ✓ Data element documentation

434 A Program makes the function call listed below. What takes place if the function raises an exception and the calling program does not list the exception in its call to the function

---

```
Call Function 'MYFUNCTION'
  exporting
    e1 = p1
  importing
    i1 = p2
```

Program is suspended

- ✓ Program continues
- Message occurs
- Runtime error

435 What is the system variable for determining how many database operations were performed

---

- ✓ sy-index
- sy-tabix
- sy-subrc
- ✓ sy-dbcnt

436 What is the Effect of not Typing Formal parameters in a Form

---

- ✓ Forms are more flexible but prone to a short dump if conversion does not work
- Forms are less flexible and are guaranteed no chance of a run time error
- Conversion never occurs
- Conversion always occurs
- No effect

437 Name the layers of the R/3 architecture.

---

**(More than one answer is correct)**

- ✓ Database
- ✓ Application
- ✓ Presentation
- Communication
- Internet

438 Which of the following allocates memory

---

- ✓ Dictionary Type
- Data Object
- Data Type
- Report Statement

439 At what point does the standard selection screen (as a result of a select-options) get displayed

---

- ✓ After Initialization event
- Prior to Initialization event
- At Start-of-Selection event
- Before the Report Statement

440 Identify the valid chaining statement

---

- Chain write ctr1 ctr2 ctr3.
- write ctr1: ctr2:ctr3.
- write ctr1, ctr2, ctr3.
- write: ctr1 ctr2 ctr3.
- ✓ Write: ctr1, ctr2, ctr3.

## TAW10 - Week 1

- 441 Refer to the following code. What is required to successfully access the individual structure fields in the FORM

---

```
Data: st_mytab like mytab.
Perform write_lines using st_mytab.
Form write_lines using rec.
  Write: / rec-field1, rec-field2.
Endform.
```

- ✓ The prefix REC is not needed
- Rec needs to be defined globally as a DATA object
- ✓ Rec needs to be defined LIKE mytab in the FORM
- The formal parameter 'rec' should be referenced by value

- 442 Which fields are used for sorting the internal table itab in the following code

---

```
Types: begin of itab_structure,
       Field1 type p,
       Field2 type c,
       Field3 type I,
       Field4 type n,
       end of itab_structure.

Data: itab type table of itab_structure.

Sort itab.
```

- ✓ Field1
- Field2, Field4
- Field1, Field3
- Field2

- 443 What happens to the program context once the user input from a dialog step has been processed

- 
- ✓ It gets rolled out
  - It remains in the buffer
  - It get rolled in
  - It remains in the database

444 What is the system variable for determining how many database operations were performed

---

- ✓  sy-subrc
- sy-index
- ✓  sy-dbcnt
- sy-tabix

445 If you want the debugger to stop when the value of 'fielda' changes. Which option would you set in the debugger

---

- Overview
- Fields
- Object
- ✓  WatchPoint

446 What does workflow achieve

---

**(More than one answer is correct)**

- ✓  automates execution of activities
- builds screen sequences
- manages communication media
- ✓  controls information flow

447 How would you determine the program name currently being executed

---

- F9
- ✓  Use menu option System>Status
- F4
- Look in the dictionary

448 What is written to the report in the following code

---

```
Data: Fielda type i value 1.  
Perform Calculate_Sales.  
Fielda = fielda + 1.
```

```
write:/ fielda.
```

```
Form Calculate_Sales.
```

```
  Data: Fielda type I value 2.
```

```
  Fielda = Fielda + 2.
```

```
Endform.
```

- 5
- ✓ 2
- 3
- 1
- 4

449 Assuming you have created a data object of type c with the name ZFIELDA in your program. Which of the following is allowed

---

- ✓ Types: ZFIELDA type I  
Data: ZFIELDA type c  
Constants: ZFIELDA type n  
Data: ZFIELDA type n

450 What is the default length for Integer Data Types

---

- 1
- size must be specified
- ✓ 4
- 2

## TAW10 - Week 1

451 What is the effect of the EXIT statement in the following code

---

```
Report ABC
Data: ..

Start-of-Selection.
Perform Form A.
End-of-Selection.

Form A.
  Loop at inttab.
    ...
    Exit.
  Endloop.
Endform.
```

- ✓ Exits the Loop
- Exits the Program
- Exits the Start-of-Selection Event
- Exits the Form

452 An ABAP program makes calls to function modules from the same function group. What happens with the Global data from the function group

---

**(More than one answer is correct)**

- ✓ The global data remains active for the duration of the function call only
- ✓ The global data is reinitialized for each new call
- ✓ Function modules from the same function group can access the global data when they are called
- ✓ The global data remains available for the duration of the calling program

453 Identify the standard methods commonly found in BAPI's

---

**(More than one answer is correct)**

CREATELIST



- ✓ UPDATEDetail
- ✓ GETLIST
- ✓ CREATEFROMDATA
- ✓ GETDETAIL

454 What clause on the Select statement is used to invoke authorization checking

---

- ✓ User Master Record
- CHECK
- Authority-check
- It is not possible

455 Where is the statement

---

- ✓ Anywhere in the program
- In a Form Only
- In a PAI Module
- In a Function

456 What is the value of result after the following code is executed

---

DATA: result TYPE I.

result = 5 / 10.

- ✓ result = 2
- result = 0
- result = 1
- result = .5

457 How much memory is reserved for the data object input\_record in the following statement.

---

```
Types: begin of rec_type,
       flag      type c,
       count(3) type c,
       today     type d,
       end of rec_type.
```

Data: input\_record type rec\_type.

- ✓ 4 bytes
- 0 bytes
- 12 bytes
- 5 bytes

458 Refer to the following code and indicate which statements are true

---

```
Data: cl_container type ref to cl_gui_custom_container,  
      cl_grid      type ref to cl_gui_alv_grid.
```

**(More than one answer is correct)**

- ✓ cl\_container points to the object that communicates with the container control
- cl\_container points to the object that communicates with the ALV grid control
- ✓ cl\_grid points to the object that communicates with the ALV grid control
- cl\_grid points to the object that communicates with the container control

459 What is the effect of sorting a sorted internal table

---

- ✓ Program abend
- Syntax error
- Breaks the sort sequence
- Uses linear search rather than binary

460 What is the default length for Integer Data Types

---

- 1
- size must be specified
- 2
- ✓ 4

## TAW10 - Week 1

- 461 At what point does the standard selection screen (as a result of a select-options) get displayed
- 
- ✓ At Start-of-Selection event  
Before the Report Statement  
After Initialization event  
Prior to Initialization event
- 462 What statement is used in ABAP programming to check if a user is authorized to perform an action
- 
- ✓ Authority-Check  
Check Authority  
Check Permission  
Check sy-subrc
- 463 Which use of the FORM statement works successfully when passing IT to FORMA
- 
- ```
Types: Begin of line,
      ...
      End of Line.
Types IT_LINE Type Standard table of line.
Data IT TYPE IT_LINE.
Perform FORMA using IT
```
- ✓ FORM FORMA Using P\_IT like IT\_LINE  
FORM FORMA Using P\_IT like LINE  
FORM FORMA Using P\_IT type IT\_LINE  
FORM FORMA Using P\_IT like LINE
- 464 Identify the rules involved when calling subroutines
- 
- ✓ Type checking is performed on parameters
- (More than one answer is correct)**

## TAW10 - Week 1

- ✓ When calling by value, the address of the actual parameter is passed to the form  
The number of actual and formal parameters must be the same  
Optional parameters are allowed

465 How could you retrieve a single entry from MYTABLE . (Key fields are number, name)

---

- ✓ Select \* from MYTABLE where number = '01' and name = 'LISA'.  
Select \* from MYTABLE where number = '01'  
Endselect.  
Select single \* from MYTABLE with keys  
Select single \* from MYTABLE where number = '01' and name = 'LISA'.

466 What is the development class for local objects

---

- ✓ \$TMP  
Local  
Z00  
Blank

467 What is written to the report in the following code

---

```
Data: Fielda type i value 1.  
Perform Calculate_Sales.  
Fielda = fielda + 1.  
write:/ fielda.
```

```
Form Calculate_Sales.  
  Data: Fielda type I value 2.  
  Fielda = Fielda + 2.  
Endform.
```

- ✓ 4  
5  
2  
1  
3

468 An Authorization Object can contain how many authorization fields

---

- ✓ unlimited
- defined by Basis
- 0
- ✓ 10

469 Refer to the following code and indicate which statements are true

---

```
Data: cl_container type ref to cl_gui_custom_container,  
      cl_grid      type ref to cl_gui_alv_grid.
```

**(More than one answer is correct)**

- ✓ cl\_container points to the object that communicates with the ALV grid control
- cl\_grid points to the object that communicates with the ALV grid control
- cl\_grid points to the object that communicates with the container control
- ✓ cl\_container points to the object that communicates with the container control

470 What is the effect when a CLEAR statement is used on an internal table without header line

---

- Nothing
- The work area is initialized
- All the lines of the table are initialized
- ✓ All the lines of the table are deleted

TAW10 - Week 1

471 How many column headers are displayed on the screen in a standard list

---

- There are no column headers
- 4
- ✓ 2
- 1

472 What statement is used to move identically named fields between structures

---

- ✓ MOVE-CORRESPONDING
- MOVE
- ASSIGN
- MOVE\_CORRESPONDING

473 How many dialog steps in an SAP Transaction.

---

- One for every explicit database commit
- One for every transaction in the SAP LUW
- Only One
- ✓ At least One

474 What requirement exists if a field is defined in the dictionary of type CURR

---

- No other requirement exists
- Decimals must be defined in the domain
- ✓ The field must be linked to another field of type CUKY
- The field must be numeric

475 What statement will clear the entire contents of the internal table itab that has no header line.

---

```
Types: begin of itab_structure,
        Field1 type p,
        Field2 type c,
        Field3 type I,
        Field4 type n,
        end of itab_structure.
```

```
Data: itab type standard table of itab_structure.
Data: wa_itab type itab_structure.
```

```

    Clear wa_itab
    Initialize wa_itab
✓   Clear itab
    Initialize itab
```

476 Identify the rules involved when calling subroutines

---

**(More than one answer is correct)**

```

✓   Type checking is performed on parameters
    When calling by value, the address of the actual paramter
    is passed to the form
✓   The number of actual and formal parameters must be the
    same
    Optional parameters are allowed
```

477 Where does the message get issued in the following.

---

```
Report ZPROGA.
Data: fielda type c.
```

```
Call Function Z_TEST_FUNCTION
    Exporting fielda = fielda
    Exceptions No_Entry = 01
              Failure   = 02.
```

```
If sy-subrc = 01.
    Message E123.
Endif.
```

```
Function Z_TEST_FUNCTION
    Importing f_fielda
    Exporting f_fieldb
    Exceptions No_Entry
              Failure
```

Message E123 Raising No\_Entry

- ✓ In Program ZPROGA  
In Program ZPROGA and Function Z\_TEST\_FUNCTION  
In Function Z\_TEST\_FUNCTION  
It will abend in the runtime system

478 What system field would you query to determine the current detail list

---

- ✓ sy-listi
- ✓ sy-list
- ✓ sy-lsind
- ✓ sy-field

479 What are valid uses of a variant .

---

**(More than one answer is correct)**

- ✓ Input validation
- ✓ Hiding input fields
- ✓ Security checking
- ✓ Pre-assigning values

480 Name the layers of the R/3 architecture.

---

**(More than one answer is correct)**

- ✓ Presentation
- Internet
- Communication
- ✓ Database
- ✓ Application



## TAW10 - Week 1

481 You are in screen painter. What is a requirement when assigning program fields to the screen

---

- the fields attributes have to be manually defined in the screen painter
- the data objects must be activated
- data objects must be activated in the dictionary
- ✓ the program must be activated

482 What is the effect of the EXIT statement in the following code

---

```
Report ABC
Data: ..

Start-of-Selection.
Perform Form A.
End-of-Selection.

Form A.
  Loop at inttab.
    ...
    Exit.
  Endloop.
Endform.
```

- Exits the Start-of-Selection Event
- Exits the Program
- Exits the Form
- ✓ Exits the Loop

483 In what case are optional parameters allowed in the passing of parameters

---

- Forms
- Neither
- Both
- ✓ Functions

484 A Table passed to a function module can be passed in what manner

- ✓ By Value
- By Exception
- By Header Line
- By Table

485 What are the tasks of the dispatcher.

---

**(More than one answer is correct)**

- ✓ assigning users to work processes
- ✓ distributing transaction load
- performing program syntax checks
- ✓ organizing communication

486 How much memory is reserved for the data object input\_record in the following statement.

---

```
Types: begin of rec_type,  
       flag      type c,  
       count(3) type c,  
       today     type d,  
       end of rec_type.
```

Data: input\_record type rec\_type.

- 5 bytes
- 4 bytes
- 0 bytes
- ✓ 12 bytes

487 Which Basis configuration would typically run on one server

---

- 2 Tier Presentation Database
- 3 Tier
- ✓ Central

488 What part of an SAP system is responsible for converting OPEN SQL statements to Native SQL

- ✓ Database Interface
- ABAP Interpreter
- Basis System
- Dispatcher
- Database Server

489 Standard and sorted tables are referred to as

---

- ✓ non unique
- index
- generic
- Unique
- keyed

490 What is the value of ZFIELDDB after the last line of the following code is executed

---

```
Data: ZFIELDA(5) type c value 'ABCDE'.  
      ZFIELDDB(4) type c.
```

```
ZFIELDA = XX .  
Clear ZFIELDA.  
ZFIELDDB = ZFIELDA.
```

- ✓ ABCD
- Spaces
- ABCDE
- BCDE

TAW10 - Week 1

491 What is true about an Authorization

---

**(More than one answer is correct)**

- ✓ An authorization is defined in the program attributes
- ✓ Defines permissible values for each authorization field listed in the authorization object
- ✓ It is attached to profiles

492 What is a client in an R/3 system

---

- ✓ Customer
- ✓ Organizational unit
- Vendor
- Delivered by Sap

493 Identify the one item that is not an ABAP Workbench tool

---

- Function Builder
- Screen Painter
- ✓ CCMS
- Menu Painter

494 What does the following statement mean Write 'Hello'(001)

---

Write 'Hello' (001)

- ✓ If Text Element 001 is not in your login language, then 'Hello' is displayed
- This is not a valid statement
- Add the variable 'Hello' to message 001
- Write out 'Hello' and the contents of text element 001

495 What statement is used to move identically named fields between structures

- ✓ MOVE
- MOVE-CORRESPONDING
- MOVE\_CORRESPONDING
- ASSIGN

496 Where can watchpoints be set

---

**(More than one answer is correct)**

- ✓ locally
- only called programs
- only the current program
- ✓ named programs

497 What internal table type can only be accessed by its key

---

- ✓ Hashed
- Keyed
- Sorted
- Standard

498 In the Catch statement, What is every runtime error assigned to

---

- ✓ Error Class
- Case
- Catch Class
- Development Class

499 What is the structure of the internal table when a select-options is declared in your program.

---

- Low High Sign Option
- High Low Sign Operator
- ✓ Sign Option Low High
- Sign Operator High Low

500 Identify developer tools that are delivered with R/3

---

**(More than one answer is correct)**

- ✓ Debugger
- ✓ SQL Trace
- ✓ CATT
- Customizing
- Dictionary Trace